

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Stone working

CS 60 WET

Order no. 374.016

**Diamond stone cutter for wet cuts, mitre cuts up to 45 °, with GFCI circuit breaker**

- High-performance motor: extra powerful for stone cutting and joint milling
- Continuous cut depth setting from 0-60 mm, with rail guide up to 54 mm. In the mitre cut from 0-44 mm, with guide rail up to 38 mm
- Continuous angle adjustment for mitre cuts from 0-45°
- Cut marking at the base plate from 0°/30°/45° for rapid orientation
- High-quality magnesium die-castings for protective cover and base plates
- Motor protection made of rubber prevents the direct intake of spray water
- Water supply: for an effective cooling of the diamond blade
- Quick-fit brass coupling: for 1/2" water hose
- GFCI operator protector circuit breaker: integrated in cord
- Ideal for: Inserting water grooves in window sills or steps, work tops, facade slabs, terazzo slabs in garden design & landscaping, joint renovation in the floor
- Spindle lock

Technical attributes	CS 60 WET
Diamond cutting disc Ø / arbor (inside Ø)	170 / 22,2 mm
Cutting depth / with guide rail	60 / 54 mm
Mitre cuttings	0-45°
Depth of cut - mitre cut	5-44 mm
Depth of cut - mitre cut with guide rail	0-38 mm
No load speed	6200 rpm
Power input	1400 watt
Power output	840 watt
Weight	4,5 kg

Standard equipment	
1 diamond cutting disc with segmented cutting edge	347.515
1 wrench for saw blade change	359.343
1 parallel guide fence	350.613
1 plastic system case	353.302
1 case insert	353.310

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Stone working

Accessories

Diamond cutting disc

With segmented cutting edge, vibration-dampened. For granite, marble, sandstone, concrete.

Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

170 Ø x 22,2	1	347.515
--------------	---	---------

With closed cutting edge for a clean wet-cut, suitable for tiles, marble plates and ceramics.

Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

170 Ø x 22,2	1	367.214
--------------	---	---------

With turbo segments for a clean wet cut; suitable for tiles and fine stoneware of any thickness up to hardness 5, marble, slate, granite and natural stone.

QTY/PKG:	Dimensions in mm:	Order no.
----------	----------------------	-----------

1	170 Ø x 22,2	386.189
---	--------------	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Stone working

Guide rail GRS

Precise aluminium profile with anodized sliding coating and guide rib.. Plugged rubber lip as contact edge at the marking, anti slip protection on the bottom. Connector 353.272 can be used to extend the guide rails as required.

Designation:	Length in mm:	QTY/PKG:	Order no.
--------------	------------------	----------	-----------

GRS 80	800	1	353.280
--------	-----	---	---------

Precise aluminium profile with anodized sliding coating and guide rib.. Plugged rubber lip as contact edge at the marking, anti slip protection on the bottom. Connector 353.272 can be used to extend the guide rails as required.

Designation:	Length in mm:	QTY/PKG:	Order no.
--------------	------------------	----------	-----------

GRS 160	1600	1	359.351
---------	------	---	---------

Connector for guide rail GRS

Precise metal connector for connecting two guide rails GRS. When not in use, the connector can be parked in the guide rail with the included tool wrench SW 5 - screw driver.

QTY/PKG:	Order no.
----------	-----------

1	353.272
---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Stone working

Plastic system case

Systainer for machine and accessories.

Size (W x L x QTY/PKG: H):	Order no.
--------------------------------	-----------

281 x 360 x 272	1	353.302
--------------------	---	---------

Insert for systainer

Insert for CSW 4161 or CS 60 WET and accessories, fits systainer 353.302.

QTY/PKG:	Order no.
----------	-----------

1	353.310
---	---------