

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Renovation machines

WST 1000 FV, Concrete-Whirljet kit

Order no. 355.771**Concrete-Giraffe® grinder for walls and ceilings**

- FV electronic control: constant speed, soft-start and overload protection
- Using a unique telescoping system, the Concrete-Giraffe® adapts to your needs. Length adjustable from 1330-1730 mm. Open telescope lock lever, pull out handle and close lever. Handle can be turned full circle
- Ergonomic design with many different handling possibilities for fatigue-free working. The motor is always kept between the gripping positions, ensuring a perfect balance
- Vacuum dust collection: protects against abrasive dust, reduces disc wear, keeps concrete pores for the new coat open
- Flexible rubber vacuum ring with low-wear metal ring: moves smoothly over the surface and protects against dust and flying stones
- Dust extraction system: with metal ring on the guard, flexible suction hose from the scouring head to the guide tube. Connection facility at the rear of the telescopic tube for FLEX industrial vacuum cleaner
- The Concrete-Giraffe® with universal joint shaft and the new grinder head have been purpose-coordinated. This tool quickly and easily removes burrs and other unevenness from walls and ceilings
- Concrete-Whirljet the grinding disc for concrete: old concrete, concrete slabs and stone - natural and artificial slabs, lime sand brick hard, paving slabs, tile glue, removing glazing from ceramic tiles. Reduced weight, with the FLEX special flange. Not to be used on edges.

Technical attributes	WST 1000 FV, Concrete-Whirljet kit
Disc Ø	125 mm
No load speed	8000 rpm
Power input	1010 watt
Power output	600 watt
Tool fixture	28 mm Ø
Dimensions in mm	1330-1730
Weight	5,50 kg

Standard equipment	
1 Concrete-Whirljet 125 Ø	323.063
1 FixTec quick-clamp nut M 14	313.459
Antistatic suction hose 32 mm Ø x 4 m with snap coupling and coupling bush for vacuum cleaner	
Carry case	1 piece

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Renovation machines

Accessories

Dry diamond disc Turbo-Jet



Turbo-Jet grinding disc for optimal stock removal. The many diamond segments means smoother working and a better finish. Also increasing the life of the machine. Ideal for deburring concrete.

Dimensions	QTY/PKG:	Order no.
in mm:		

125 Ø x 28 x 23,5	1	349.623
-------------------	---	---------

Thermo-Jet dry diamond grinding disc



Thermo-Whirljet for thin coatings and lightly abrasive materials: Thermoplastic coatings, Paint, Graffiti, thin glue residues on concrete or screed, Rubber based coatings. Reduced weight with the FLEX flange. The grinding disc with the angular arranged diamond segments allows for a quicker work rate than with normal disc. The large dimensioned delta shaped holes in the discs causes an air vortex that removes all dust from the working surface and prevents the segments from clogging or overheating and so reducing wear. The leight weight disc reduces wear on the motor. Not for use on edges.

Dimensions	QTY/PKG:	Order no.
in mm:		

125 Ø x 28 x 23,5	1	323.071
-------------------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Renovation machines

Screed-Jet dry diamond grinding disc



Screed-Whirljet for abrasive materials: Abrasive screeds (with quartz sand), fresh concrete, plaster, abrasive limestone (with quartz sand) sandstone, fire clay, asphalt. Reduced weight, with FLEX special flange. Not to be used for working on edges.

Dimensions	QTY/PKG:	Order no.
------------	----------	-----------

in mm:

125 Ø x 28 x 23,5	1	324.361
-------------------	---	---------

Concrete-Jet dry diamond grinding disc



Concrete-Whirljet the grinding disc for concrete: old concrete, concrete slabs and stone - natural and artificial slabs, lime sand brick hard, paving slabs, tile glue, removing glazing from ceramic tiles. Reduced weight, with the FLEX special flange. Not to be used on edges.

Dimensions	QTY/PKG:	Order no.
------------	----------	-----------

in mm:

125 Ø x 28 x 23,5	1	323.063
-------------------	---	---------

Rubber extraction rings



The flexible rubber vacuum ring moves smoothly over the surface and provides optimum protection against dust and flying stones.

Dimensions	QTY/PKG:	Order no.
------------	----------	-----------

in mm:

125 Ø	1	257.246
-------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Renovation machines

Concrete grinder head without disc



Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

125 Ø	1	350.931
-------	---	---------

Snap-ring grey



For suction hose SH-C with snap coupling.

QTY/PKG:	Order no.
----------	-----------

1	379.654
---	---------