

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Mixers

### MXE 900 + WR2 120

**Order no. 387.886**

Technical attributes	MXE 900 + WR2 120
No load speed	200-750 rpm
Power input	900 watt
Power output	520 watt
Tool fixture	M 14
Clamping neck Ø	43 mm
Max. mixing paddle Ø	120 mm
Size ( W x L x H )	360 x 235 x 315 mm
Weight (with mixing paddle)	5,1 kg

Standard equipment	
1 WR2 helix paddle 120x600 M14	368.989
1 open-ended wrench SW 19	
1 open-ended wrench SW 22	

#### 900 watt single gear mixer

- Large, rugged single-speed gear unit with optimum gear ratio for high torque
- The soft start accelerator switch smoothly adjusts the speed to the mixing situation and material

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

# FLEX

## Mixers

- Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation. With anti-slip coating
- Four corner guards with rubber buffer and inserted metal plate provide secure storage during transportation and offer protection against shocks and impacts at the building site
- Protective cap above the motor housing guides the cooling air flow and prevents the ingress of rain water
- The flexible rubber grommet over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- With 4 metres H07-RNF cable
- Perfect for mixing low-quantity mixtures up to 25 kg. Thus mixer is ideal for tilers and painters
- With mixing paddle for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...
- This machine is also available in 110 V

### Accessories

#### Spiral paddle RR2



Two negatively arranged spirals force the material down, preventing the liquid material from splashing. Ideal for mixing liquid to tough material: Paint, emulsions, varnishes, glazes, coatings, paste, bitumen.

Paddle in mm:	Mix in kg:	QTY/PKG:	Order no.
------------------	------------	----------	-----------

120 Ø	20-40	1	368.903
-------	-------	---	---------

#### Helix paddle WR2



Two clockwise helices for kneading and mixing tough to pasty materials. The mixer paddle screws itself down forcing the material upwards. Extremely versatile, can be used for: tile adhesive, grout, filler, finished plaster, adhesive mortar, filler compound, floor screed.

Paddle in mm:	Mix in kg:	QTY/PKG:	Order no.
------------------	------------	----------	-----------

120 Ø	15-25	1	368.881
-------	-------	---	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Mixers

**Helix paddle WR3R**

Three clockwise helices screw themselves into the material. This provides fast, intensive mixing of even the heaviest and toughest mixtures, with little effort. Also known as a mortar or tough mixture paddle. Ideal for: mortar, concrete, plaster, screed, plasterboard bonding compound, bitumen coating.

Paddle in mm:	Mix in kg:	QTY/PKG:	Order no.
------------------	------------	----------	-----------

120 Ø	15-25	1	368.911
-------	-------	---	---------

**Helix paddle WR3L**

Three anticlockwise helices press down the mix in the container. Any deposited pigments, solids or fibres are forced upwards and evenly mixed. The mix does not splash. Ideal for liquid and creamy mix: paints, emulsion paints, gypsum plaster, casting compounds, fibrous materials.

Paddle in mm:	Mix in kg:	QTY/PKG:	Order no.
------------------	------------	----------	-----------

120 Ø	15-25	1	369.055
-------	-------	---	---------

**Disc paddle SR2**

Two discs with counter-running angled blades create a dynamic flow in the mixing container. The blades on the discs force the material being mixed in opposing directions downwards or upwards. Ideal for mixing liquid to tough material: Paint, emulsion, paste, glue, jointing mortar.

Paddle in mm:	Mix in kg:	QTY/PKG:	Order no.
------------------	------------	----------	-----------

120 Ø	15-25	1	368.938
-------	-------	---	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Mixers

**Beater RB**

Round mixing arms prevent air bubbles from being mixed in. Ideal for all materials where air pockets are to be avoided: filler compounds, fillers, adhesives, sealants.

Paddle in mm:	Mix in kg:	QTY/PKG:	Order no.
------------------	------------	----------	-----------

120 Ø	10-30	1	369.152
-------	-------	---	---------