

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Mixers

R 600 VV

Order no. 282.359

Technical attributes	R 600 VV
No load speed	150-500 rpm
Power input	1300 watt
Power output	850 watt
Tool fixture	M 18
Clamping neck Ø	63 mm
Max. mixing paddle Ø	160 mm
Weight	5,4 kg

Standard equipment	
1 handle (long)	259.538
1 helix paddle WR3R 160x600 M14	369.020
1 adapter M 18 x M 14	250.484
1 open-ended wrench SW 24	198.781

1300 watt mixer with speed selection

- VV electronic control: with constant speed control, soft start with continuous speed accelerator switch, overload protection and speed selector wheel
- Mixing head adapter: M 18, with adapter M 14
- Stable safety and deposit hoop: Protects the machine from dirt and damage
- Long side handgrip for fatigue-free and safety torque take-up
- Spade handle with integrated switch for maximum operator convenience
- Ideal for mixing paint, stiff adhesives, solvents and insulation compounds in continuous use
- Rugged and long-life for heavy-duty use

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Mixers

- This machine is also available in 110 V

Accessories

M 18 to M 14 adapter

For attaching FLEX mixing paddles M 14 to FLEX R 600, R 600 VV and R 1800 VR mixers.



QTY/PKG:	Order no.
----------	-----------

1	250.484
---	---------

Helix paddle WR2



Two clockwise helices for kneading and mixing tough to pasty materials. The mixer paddle screws itself down forcing the material upwards. Extremely versatile, can be used for: tile adhesive, grout, filler, finished plaster, adhesive mortar, filler compound, floor screed.

Paddle in mm:	Mix in kg:	QTY/PKG:	Order no.
---------------	------------	----------	-----------

140 Ø	20-40	1	368.997
-------	-------	---	---------

160 Ø	20-40	1	369.004
-------	-------	---	---------

Helix paddle WR3R



Three clockwise helices screw themselves into the material. This provides fast, intensive mixing of even the heaviest and toughest mixtures, with little effort. Also known as a mortar or tough mixture paddle. Ideal for: mortar, concrete, plaster, screed, plasterboard bonding compound, bitumen coating.

Paddle in mm:	Mix in kg:	QTY/PKG:	Order no.
---------------	------------	----------	-----------

140 Ø	20-40	1	369.012
-------	-------	---	---------

160 Ø	30-60	1	369.020
-------	-------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Mixers

Helix paddle WR3L

Three anticlockwise helices press down the mix in the container. Any deposited pigments, solids or fibres are forced upwards and evenly mixed. The mix does not splash. Ideal for liquid and creamy mix: paints, emulsion paints, gypsum plaster, casting compounds, fibrous materials.

Paddle in mm:	Mix in kg:	QTY/PKG:	Order no.
------------------	------------	----------	-----------

140 Ø	20-40	1	369.063
-------	-------	---	---------

160 Ø	30-60	1	369.071
-------	-------	---	---------

Disc paddle SR2

Two discs with counter-running angled blades create a dynamic flow in the mixing container. The blades on the discs force the material being mixed in opposing directions downwards or upwards. Ideal for mixing liquid to tough material: Paint, emulsion, paste, glue, jointing mortar.

Paddle in mm:	Mix in kg:	QTY/PKG:	Order no.
------------------	------------	----------	-----------

140 Ø	20-40	1	369.128
-------	-------	---	---------

160 Ø	30-60	1	369.136
-------	-------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Mixers

Beater RB

Round mixing arms prevent air bubbles from being mixed in. Ideal for all materials where air pockets are to be avoided: filler compounds, fillers, adhesives, sealants.

Paddle in mm:	Mix in kg:	QTY/PKG:	Order no.
------------------	------------	----------	-----------

140 Ø	30-60	1	369.160
-------	-------	---	---------