

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Measuring technology/Laser

### ALC 3/1-Basic

Order no. 409.243



Technical attributes	ALC 3/1-Basic
Number of lines	1 horizontal/2 vertical plus plumb
Visible area lines	90°
Precision	± 0.3 mm/m (plumb ± 0,6 mm/m)
Self-levelling range	± 4 °
Max. working range	20 m / plumb 5 m
Operation duration	6 h
Temperature range	-5° - +50 °C
Laser class	2
Weight	0,58 kg

**Standard equipment**

1 wall holder magnetic

Batteries 3x AA

1 padded carrying bag

**Self-levelling crossline laser**

- With one horizontal and two vertical laser lines at a 90° angle plus plumb, can be switched individually
- Plumb function
- The exceptionally bright laser lines are still highly visible even in poor light conditions
- Self-levelling
- Optical warning signal when self-levelling range exceeded
- Self-levelling which can be switched off
- Simple On-button operation
- Transportation lock
- 1/4" thread for tripod
- Ideal for aligning the framework

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Measuring technology/Laser

### Accessories

#### Laser target plate



Amplifies the projection of the red laser beam over long distances or in a bright environment. Magnetic and can be set up.

QTY/PKG:	Order no.
----------	-----------

1	393.606
---	---------

#### Wall and ceiling mount



Adjustable wall and ceiling holder with additional clamping function. 1/4" device connection.

QTY/PKG:	Order no.
----------	-----------

1	393.614
---	---------

#### Laser wall holder



Magnetic 90° wall holder made of aluminium with 1/4" device connection.

QTY/PKG:	Order no.
----------	-----------

1	393.630
---	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Measuring technology/Laser

### Laser tripod adapter

---



5/8" internal thread on 1/4" external thread for using the laser on the elevator tripod (398.616).

QTY/PKG:	Order no.
----------	-----------

---

1	398.608
---	---------