

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Safety vacuum cleaner construction/workshop class

VC 35 L MC

Order no. 369.799

Technical attributes	VC 35 L MC
Power input P. max.	1380 watt
Max. volume flow	3660 l/min
Max. vacuum	23000 Pa
Filter surface	6150 cm ²
Container volume	34 l
Capacity liquid	19 l
Power take off	100-2200 watt
Size (W x L x H)	505 x 380 x 580 mm
Weight	9,5 kg

Standard equipment	
4 m suction hose 32 mm Ø with 32/28 mm Ø adapter, 25-32 mm Ø universal adapter and suction hose extension	297.011
1 filter bag	1 piece of 296.961
1 flat-fold filter class M	337.692
1 elbow	297.038
2x 0,5 m metal vacuum tube	300.691 (2x)
1 clip floor nozzle complete with replacement insert (brush, rubber strip)	300.659
1 crevice nozzle	259.697

Safety vacuum cleaner with manual filter cleaning system, 34 l, class L

- The high-performance turbine ensures both a high suction capacity and a high vacuum. The outcome is an excellent extraction result
- Patented filter vibration: vibration at the press of a button on the vacuum hose
- The flat-fold filter design is such that the container capacity can be optimally used for dust and dirt
- Suitable for wet vacuuming: with electronic liquid level control
- With appliance socket and electronic automatic switch on/off
- Soft start stops any voltage peaks at the start and the run-on feature (15 sec. overrun) empties any remaining dust in the vacuum hose
- Scope for tool storage on top of vacuum cleaner and accessories depot for suction nozzles and tubes at the back
- Equipped with large wheels and two swivel guide rollers
- Suitable for increased stress when used commercially. Ideal for cleaning work in offices, storage rooms, workshops and vehicles. Smaller electric power tools, e.g. palm sander, delta sander, random-orbit sander, jigsaws, are primarily used for extraction work. Tools which produce fairly low amounts of dust
- Safety vacuum cleaner, approved for dust class L, suitable for all dust with OEL value >1 mg/m³