

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Stone working

LE 12-3 100 WET, PRCD

Order no. 378.461**1150 watt wet stone grinder with variable speed, with GFCI circuit breaker, 115 mm**

- Powerful 1150 W motor
- VR full-wave electronic control: tachogenerator constant speed control, soft start, overload protection and speed selection
- High torque for maximum material removal and optimum surface quality
- Powder-coated and varnished magnetic pad for a long service life, thanks to the additional protection against wear and abrasive dust
- Grip hood for easy handling and precise working
- Bail handle: Secure grip, even when working on vertical surfaces
- The new water feed and control system is located below the housing, which makes operation and precise dosing easy. An unobstructed grip area is provided directly above the backing pad
- 2 m special hose: No additional hose safety devices required. Increases flexibility, reduces weight and prevents risk of injury from hose clips
- Quick-fit brass coupling: for 1/2" water hose
- GFCI operator protector circuit breaker: integrated in cord
- Spindle lock
- This machine is also available in 110 V

Technical attributes	LE 12-3 100 WET, PRCD
Max. disc diameter	115 mm
No load speed	1200-3700 rpm
Power input	1150 watt
Power output	700 watt
Tool fixture	M 14
Size (L x H)	340 x 140 mm
Connecting hose with quick coupling	2 m
Weight	2,4 kg

Standard equipment

1 bail handle

1 hook-and-loop cable ties

Accessories**Rubber coupling**

For all applications where a smooth sanding is required. Adapts itself together with the velcro backing pad flexibly to the surface of the workpiece. Is screwed on as an adapter between the M14 machine connection and the velcro backing pad.

QTY/PKG: Order no.**1 240.338**

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Stone working

Hollow diamond drill bit



M 14, wet, for natural stone and fine stoneware tiles.

D in mm:	T in mm:	L in mm:	QTY/PKG:	Order no.
6 Ø	58	88	1	315.052
8 Ø	73	103	1	315.060
10 Ø	88	118	1	315.079
12 Ø	98	128	1	315.087
14 Ø	113	143	1	315.095

Velcro pad, soft



For secure attachment of the velcro diamond discs. M 14 connection.

Dimensions in mm:	QTY/PKG:	Order no.
100 Ø	1	253.814

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Stone working

Dia-Jet velcro diamond discs wet (single)



For grinding and polishing: Suitable for artificial stone, natural stone, stoneware and ceramics. The grinding output of the diamond discs is higher than that of traditional abrasives, they have a very long service life and high mechanical resilience.

Dimensions in mm:	Grit:	colour:	QTY/PKG:	Order no.
100 Ø	grit 60	dark green	1	253.815
100 Ø	grit 100	blue	1	253.816
100 Ø	grit 200	light green	1	253.817
100 Ø	grit 400	yellow	1	253.818
100 Ø	grit 800	orange	1	253.819
100 Ø	grit 1500	red	1	253.820
100 Ø	grit 3000	brown	1	253.821
100 Ø	grit 10000	black	1	253.822

Dia-Jet velcro diamond discs wet in a set



Set with 5 grains. For grinding and polishing.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
100 Ø	grit 100 - 1500	5	253.823

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Stone working

Diamond hollow hole drill bits



The hollow hole drill bits are suitable for use on machines with integrated water supply and M 14 spindle thread. Vibration-free drilling in tiles (all hardnesses), fine stoneware (up to hardness 5), natural stone, granite.

Diameter in mm:	Length in mm:	QTY/PKG:	Order no.
5	30	1	386.359
6	30	1	386.367
8	30	1	386.375
10	30	1	386.383