

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Stone working

L 12-3 100 WET, PRCD

Order no. 378.488



1150 watt wet stone grinder with GFCI circuit breaker, 115 mm

- Powerful 1150 W motor
- FR full-wave electronic control: tachogenerator constant speed control, soft start, overload protection
- High torque for maximum material removal and optimum surface quality
- Powder-coated and varnished magnetic pad for a long service life, thanks to the additional protection against wear and abrasive dust
- Grip hood for easy handling and precise working
- Bail handle: Secure grip, even when working on vertical surfaces
- The new water feed and control system is located below the housing, which makes operation and precise dosing easy. An unobstructed grip area is provided directly above the backing pad
- 2 m special hose: No additional hose safety devices required. Increases flexibility, reduces weight and prevents risk of injury from hose clips
- Quick-fit brass coupling: for 1/2" water hose
- GFCI operator protector circuit breaker: integrated in cord
- Spindle lock
- This machine is also available in 110 V

| Technical attributes | L 12-3 100 WET, PRCD |
|-------------------------------------|-------------------------|
| Max. disc diameter | 115 mm |
| No load speed | 3700 rpm |
| Power input | 1150 watt |
| Power output | 700 watt |
| Tool fixture | M 14 |
| Size (L x H) | 340 x 140 mm |
| Connecting hose with quick coupling | 2 m |
| Weight | 2,4 kg |

Standard equipment

- 1 bail handle
- 1 hook-and-loop cable ties

Accessories

Rubber coupling



For all applications where a smooth sanding is required. Adapts itself together with the velcro backing pad flexibly to the surface of the workpiece. Is screwed on as an adapter between the M14 machine connection and the velcro backing pad.

| QTY/PKG: | Order no. |
|----------|-----------|
| 1 | 240.338 |

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Stone working

Velcro pad, soft

For secure attachment of the velcro diamond discs. M 14 connection.



| Dimensions in mm: | QTY/PKG: | Order no. |
|----------------------|----------|-----------|
| 100 Ø | 1 | 253.814 |

Dia-Jet velcro diamond discs wet (single)

For grinding and polishing: Suitable for artificial stone, natural stone, stoneware and ceramics. The grinding output of the diamond discs is higher than that of traditional abrasives, they have a very long service life and high mechanical resilience.



| Dimensions in mm: | Grit: | colour: | QTY/PKG: | Order no. |
|----------------------|------------|-------------|----------|-----------|
| 100 Ø | grit 60 | dark green | 1 | 253.815 |
| 100 Ø | grit 100 | blue | 1 | 253.816 |
| 100 Ø | grit 200 | light green | 1 | 253.817 |
| 100 Ø | grit 400 | yellow | 1 | 253.818 |
| 100 Ø | grit 800 | orange | 1 | 253.819 |
| 100 Ø | grit 1500 | red | 1 | 253.820 |
| 100 Ø | grit 3000 | brown | 1 | 253.821 |
| 100 Ø | grit 10000 | black | 1 | 253.822 |

Dia-Jet velcro diamond discs wet in a set



Set with 5 grains. For grinding and polishing.

| Dimensions in mm: | Grit: | QTY/PKG: | Order no. |
|----------------------|--------------------|----------|-----------|
| 100 Ø | grit 100 - 1500 | 5 | 253.823 |

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Stone working

Diamond hollow hole drill bits



The hollow hole drill bits are suitable for use on machines with integrated water supply and M 14 spindle thread. Vibration-free drilling in tiles (all hardnesses), fine stoneware (up to hardness 5), natural stone, granite.

| Diameter in mm: | Length in mm: | QTY/PKG: | Order no. |
|--------------------|------------------|----------|-----------|
| 5 | 30 | 1 | 386.359 |
| 6 | 30 | 1 | 386.367 |
| 8 | 30 | 1 | 386.375 |
| 10 | 30 | 1 | 386.383 |