

Tetrix 300 Classic TM

090-000098-00502



WE ARE WELDING



- Modular DC TIG inverter welding machine, gas- or water-cooled
- Features characteristics for EWM activArc and EWM spotArc at no extra charge
- TIG welding with reproducible, electronic HF start
- TIG lift arc welding without HF
- Non-latched/latched operation
- Clearly structured operating panel, operating elements streamlined to feature the main TIG functions
- Key functions can be adjusted conventionally using a potentiometer and rotary transducer
- TIG pulse function
- Reduced secondary current accessible using torch trigger
- Spot welding/tack function (spotArc/spotmatic)
- Up-slope/down-slope adjustable
- Spotmatic – halves time required for tacking
- Adjustable gas pre-flows/post-flows
- **MMA welding**
- MMA average value pulsing
- Ideal for root welding
- Safe, reliable vertical-up and vertical-down welding
- Adjustable hot start current and hot start time
- Adjustable Arcforce
- Antistick function
- Safe ignition also for long hose packages
- Gas-cooled or optionally water-cooled with cool 35 U31 cooling unit
- Excellent torch cooling, resulting in cost savings on consumables due to high-performance centrifugal pump and 4.5-litre water tank (cool 35 U31 cooling unit)
- Energy-saving thanks to high efficiency and standby function
- High mains voltage tolerances and therefore fully generator-compatible
- Connection capability for remote control and function torch
- Trolley 35.2-2 trolley available for delivery
- Mains connection 3 x 400 V/16 A
- **Scope of supply includes welding machine only; other components such as trolley and cooling unit can be selected from accessories!**

	TIG		MMA	
Setting range for welding current	5 A - 300 A			
Duty cycle at ambient t.e	40 °C	25 °C	40 °C	25 °C
60 %	300 A	–	300 A	–
80 %	–	300 A	–	300 A
100 %	250 A	270 A	250 A	270 A
Open circuit voltage	98 V			
Mains frequency	50 Hz / 60 Hz			
Mains fuses (slow-blow)	3 x 16 A			
Mains voltage (tolerances)	3 x 400 V (-25 % - +20 %)			
Max. connected load	8.3 kVA		12.1 kVA	
Recommended generator power	11.2 kVA		16.3 kVA	
cos φ	0.99			
Efficiency	88 %			
Dimensions machine, LxWxH in mm	590 x 230 x 380			
Weight, machine	29 kg			
Torch connection	Decentral			

12.06.2018

Welding site equipment for TIG welding

cool35 U31

090-008235-00502



- Cooling unit for water-cooled welding torches
- Modular design, tool-free assembly
- Cooling capacity 1 l/min: 800 W, max. flow rate: 5 l/min, max. output pressure: 3.5 bar, 4.5 l tank capacity
- Dimensions L x W x H in mm, 600 x 270 x 225 Weight 15 kg

TIG 200 GRIP GD 5P 4m

394-510981-00600



- Gas-cooled TIG welding torch
- Double push-button
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 11 mm, size 7
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 260 GRIP WD 5P 4m

394-510990-00600



- Water-cooled TIG welding torch
- Double push-button
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 10 mm, size 8
- Tungsten electrode E3 (purple): Ø 2.4 mm

KF 23E-10, -10

094-000530-00000



- Coolant (-10 °C), 9.3 l

Welding site equipment for TIG welding

Trolly 35.2-2

090-008296-00000



- Transport cart
- Solid, stable design
- For transporting a power source, a cooling unit and a gas cylinder
- Can be lifted by crane (option ON CS Trolly 35.2-2 required)

OW CEE 16A/400V

092-008214-00000



- Factory fitting (no retrofitting)

WK50mm² 350A/60% 4m/K

092-000003-00000



- Completely assembled workpiece lead with terminal

DM 842 Ar/CO₂ 230bar 15l D

394-002910-00015



- Manufactured in accordance with ISO 2503
- Maximum primary pressure of 230 bar
- Single-stage
- Infinite and highly accurate adjustment
- Safety manometer with pressure meter or flow meter (bar/psi or litres per minute)
- With cut-off valve

Gas hose

094-000010-00001



- Equipped with plastic nuts on both sides for tool-free assembly

Accessories

ON 19pol Tetrix 300/351(AC)

092-001827-00000



- 19-pole connection socket for accessory components and/or as analog interface for automated welding

cool35 U31

090-008235-00502



- Cooling unit for water-cooled welding torches
- Modular design, tool-free assembly
- Cooling capacity 1 l/min: 800 W, max. flow rate: 5 l/min, max. output pressure: 3.5 bar, 4.5 l tank capacity
- Dimensions L x W x H in mm, 600 x 270 x 225 Weight 15 kg

SPOTARC TIG 26 G 5P 4m

094-500046-00000



- Spot welding torch, with welding nozzles for fillet welds, edge welds and flat welds incl. setting gauge
- Better surface formation in comparison to resistance welding
- Flatter spot formation in comparison to MAG spot welding
- Excellent seam quality due to minimal heat input
- Very low thermal stresses and little distortion due to short welding times
- Perfect for visible joints due to clean seam appearance
- Robust design
- Excellent HF safety
- **Equipment as delivered:**
- Collet body: Ø 2.4 mm

SPOTARC TIG 18 W 5P 4m

094-500048-00000



- Spot welding torch, with welding nozzles for fillet welds, edge welds and flat welds incl. setting gauge
- Better surface formation in comparison to resistance welding
- Flatter spot formation in comparison to MAG spot welding
- Excellent seam quality due to minimal heat input
- Very low thermal stresses and little distortion due to short welding times
- Perfect for visible joints due to clean seam appearance
- Robust design
- Excellent HF safety
- **Equipment as delivered:**
- Collet body: Ø 2.4 mm

Accessories

TIG 200 GRIP GD 5P 4m

394-510981-00600



- Gas-cooled TIG welding torch
- Double push-button
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 11 mm, size 7
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 200 GRIP GD 5P HFL 4m

394-510981-10600



- Gas cooled TIG welding torch with a highly flexible hose package
- Double push-button
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 11 mm, size 7
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 260 GRIP WD 5P 4m

394-510990-00600



- Water-cooled TIG welding torch
- Double push-button
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 10 mm, size 8
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 260 GRIP WD 5P HFL 4m

394-510990-10600



- Water cooled TIG welding torch with a highly flexible hose package
- Double push-button
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 10 mm, size 8
- Tungsten electrode E3 (purple): Ø 2.4 mm

Accessories

TIG 200 GRIP GD 8P U/D 4m

394-510981-00200



- Gas-cooled TIG welding torch
- Setting of welding current and programs
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Suitable for devices from the Tetrix DC and AC/DC series
- An 8-pole connection socket is required for portable machines
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 11 mm, size 7
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 200 GRIP GD 8P U/D HFL 4m

394-510981-10200



- Gas cooled TIG welding torch with a highly flexible hose package
- Setting of welding current and programs
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Suitable for devices from the Tetrix DC and AC/DC series
- An 8-pole connection socket is required for portable machines
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 11 mm, size 7
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 260 GRIP WD 8P U/D 4m

394-510990-00200



- Water-cooled TIG welding torch
- Setting of welding current and programs
- Ergonomic GRIP handle for a secure grip
- Suitable for devices from the Tetrix DC and AC/DC series
- An 8-pole connection socket is required for portable machines
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 10 mm, size 8
- Tungsten electrode E3 (purple): Ø 2.4 mm

Accessories

TIG 260 GRIP WD 8P U/D HFL 4m

394-510990-10200



- Water cooled TIG welding torch with a highly flexible hose package
- Setting of welding current and programs
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Suitable for devices from the Tetrix DC and AC/DC series
- An 8-pole connection socket is required for portable machines
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 10 mm, size 8
- Tungsten electrode E3 (purple): Ø 2.4 mm

Trolley 35.2-2

090-008296-00000



- Transport cart
- Solid, stable design
- For transporting a power source, a cooling unit and a gas cylinder
- Can be lifted by crane (option ON CS Trolley 35.2-2 required)

Trolley 38-2 E

090-008270-00000



- Transport cart
- For Tetrix 230, 270, 300, 300-2, 400-2 DC as well as Tetrix 230, 300 AC/DC
- Solid, stable design
- For transporting a power source, a cooling unit and a gas cylinder
- Dimensions L x W x H in mm, 818 x 533 x 1233 Weight 35 kg

RTG1 19POL 5m

090-008106-00000



- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- With pre-fitted 5 or 10 m connection cable
- Operating point setting directly at the site of welding
- For Tetrix, Picotig 200 AC/DC and Stick machine series

Accessories

RT1 19POL

090-008097-00000



- Remote control, current
- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- Operating point setting directly at the site of welding
- Robust metal casing with rubber feet, retaining clip and holding magnet

RTP1 19POL

090-008098-00000



- Remote control, pulse, spot and pause times are infinitely adjustable.
- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- Pulse/spot/normal
- Operating point setting directly at the site of welding
- Robust metal casing with rubber feet, retaining clip and holding magnet
- For Tetrix and Picotig 200 AC/DC machine series

RTP2 19POL

090-008099-00000



- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- Pulse/spot/normal
- Frequency and spot times infinitely adjustable.
- Coarse adjustment of the cycle frequency.
- Pulse/pause ratio (balance) adjustable from 10% to 90%.
- Operating point setting directly at the site of welding
- Robust metal casing with rubber feet, retaining clip and holding magnet
- For Tetrix and Picotig 200 AC/DC machine series

RTP3 spotArc 19POL

090-008211-00000



- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- Remote control, pulse / spotArc spot welding / normal
- Frequency and spot times infinitely adjustable.
- Coarse adjustment of the cycle frequency.
- Pulse/pause ratio (balance) adjustable from 10% to 90%.
- Operating point setting directly at the site of welding
- Robust metal casing with rubber feet, retaining clip and holding magnet
- For Tetrix and Picotig 200 AC/DC machine series

Accessories

RTF1 19POL 5 M

094-006680-00000



- Foot-operated remote control, start/stop
- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- Start/stop welding operation
- Operating point setting directly at the site of welding

OW CEE 16A/400V

092-008214-00000



- Factory fitting (no retrofitting)

5POLE/CEE/16A/M

094-000712-00000



- Mains plugs

WK25mm² 230A/60% 4m FIX

398-000593-00000



- Completely assembled workpiece lead with original FIX clamp

WK95mm² 550A/60% 4m/Z

092-000171-00000



- Komplet montierte Werkstückleitung mit Zwing

Accessories

WK35mm² 290A/60% 4m/K
092-000008-00000



- Completely assembled workpiece lead with terminal

EH 50qmm 4m
092-000004-00000



- Fully assembled electrode holder with cable

ON AL D13/27
092-003282-00000



- Cap for load sockets

Gas hose
094-000010-00005



- Equipped with plastic nuts on both sides for tool-free assembly

L-BOXX 374
094-003899-00000



- Robuste Transportbox

L-BOXX 102
094-003900-00000



- Robuste Transportbox