

Tetrix 300 Comfort 2.0 puls 8P TM

090-000238-00504



WE ARE WELDING



- Modular DC TIG inverter welding machine, gas- or water-cooled
- Comfort 2.0 control, simple operation with click wheel
- **TIG welding**
 - Features characteristics for EWM activArc and EWM spotArc at no extra charge
 - TIG welding with reproducible, electronic HF start
 - TIG lift arc welding without HF
 - TIG average value pulsing: the preset welding current is maintained at all times, so particularly suitable for welding as per welding procedure specification
 - TIG automated pulsing with automatic specification of required pulse parameters
 - Pulsed TIG welding in Hz and kHz range up to 15 kHz
 - 8 programmed JOBs (welding tasks)
 - Non-latched/latched operation
 - Reduced secondary current accessible using torch trigger
 - Spot welding/tack function (spotArc/spotmatic)
 - spotmatic and spotArc with direct access
 - Up-slope/down-slope adjustable
 - Adjustable gas pre-flows/post-flows
- **MMA welding**
 - MMA average value pulsing
 - Ideal for root welding
 - 8 programmed JOBs (welding tasks)
 - Safe, reliable vertical-up and vertical-down welding
 - Adjustable hot start current and hot start time
 - Adjustable Arcforce
 - Antistick function
- **Highlights**
 - Safe ignition also for long hose packages
 - Gas-cooled or optionally water-cooled with cool 41 U31 cooling unit
 - Excellent torch cooling, resulting in cost savings on consumables due to high-performance centrifugal pump and 4-litre water tank (cool 41U31 cooling unit)
 - Energy-saving thanks to high efficiency and standby function
 - High mains voltage tolerances and therefore fully generator-compatible
 - Connection capability for remote control and function torch
 - Trolley 35.2-2 trolley available for delivery
 - Can be optionally connected to LAN or WiFi. Xnet-compatible
 - PC interface for PC300.Net software
 - **Scope of supply includes welding machine only; other components such as trolley and cooling unit can be selected from accessories!**

	TIG	MMA
Setting range for welding current	5 A - 300 A	
Duty cycle at ambient t.e	40 °C	
30 %	—	300 A
35 %	300 A	—
60 %	260 A	
100 %	210 A	
Open circuit voltage	63 V	
Mains frequency	50 Hz / 60 Hz	
Mains fuses (slow-blow)	3 x 16 A	
Mains voltage (tolerances)	3 x 400 V (-25 % - +20 %)	
Max. connected load	12.1 kVA	12 kVA

12.06.2018

Recommended generator power	16.3 kVA	16.4 kVA
cos φ	0.99	
Efficiency	88 %	
Dimensions machine, LxWxH in mm	539 x 210 x 415	
Weight, machine	20 kg	
Torch connection	Decentral	

Welding site equipment for TIG welding

cool41 U31

090-008600-00502



- Cooling unit for water-cooled welding torches
- Modular design, tool-free assembly
- Cooling capacity 1 l/min: 800 W, max. flow rate: 5 l/min, max. output pressure: 3.5 bar, 4.0 l tank capacity
- Dimensions L x W x H in mm, 600 x 210 x 340. Weight: 18.4 kg

TIG 200 GRIP GD 8P U/D 4m

394-510981-00200



- Gas-cooled TIG welding torch
- Setting of welding current and programs
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Suitable for devices from the Tetrix DC and AC/DC series
- An 8-pole connection socket is required for portable machines
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 11 mm, size 7
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 260 GRIP WD 8P U/D 4m

394-510990-00200



- Water-cooled TIG welding torch
- Setting of welding current and programs
- Ergonomic GRIP handle for a secure grip
- Suitable for devices from the Tetrix DC and AC/DC series
- An 8-pole connection socket is required for portable machines
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 10 mm, size 8
- Tungsten electrode E3 (purple): Ø 2.4 mm

KF 23E-10, -10

094-000530-00000



- Coolant (-10 °C), 9.3 l

Welding site equipment for TIG welding

Trolly 35.2-2

090-008296-00000



- Transport cart
- Solid, stable design
- For transporting a power source, a cooling unit and a gas cylinder
- Can be lifted by crane (option ON CS Trolly 35.2-2 required)

OW CEE 16A/400V

092-008214-00000



- Factory fitting (no retrofitting)

WK50mm² 350A/60% 4m/K

092-000003-00000



- Completely assembled workpiece lead with terminal

DM 842 Ar/CO₂ 230bar 15l D

394-002910-00015



- Manufactured in accordance with ISO 2503
- Maximum primary pressure of 230 bar
- Single-stage
- Infinite and highly accurate adjustment
- Safety manometer with pressure meter or flow meter (bar/psi or litres per minute)
- With cut-off valve

Gas hose

094-000010-00001



- Equipped with plastic nuts on both sides for tool-free assembly

Accessories

ON FILTER TIG 40

092-002551-00000



- Dirt filter for air inlet
- Reliably protects the machine from impurities under tough working conditions.

ON PC PLUG

092-003074-00000



- Protective cap for plug
- Protects against force exerted from left, right or above

cool41 U31

090-008600-00502



- Cooling unit for water-cooled welding torches
- Modular design, tool-free assembly
- Cooling capacity 1 l/min: 800 W, max. flow rate: 5 l/min, max. output pressure: 3.5 bar, 4.0 l tank capacity
- Dimensions L x W x H in mm, 600 x 210 x 340. Weight: 18.4 kg

FRV 7POL 15m

092-000201-00005



- Connection cable extension

SPOTARC TIG 26 G 5P 4m

094-500046-00000



- Spot welding torch, with welding nozzles for fillet welds, edge welds and flat welds incl. setting gauge
- Better surface formation in comparison to resistance welding
- Flatter spot formation in comparison to MAG spot welding
- Excellent seam quality due to minimal heat input
- Very low thermal stresses and little distortion due to short welding times
- Perfect for visible joints due to clean seam appearance
- Robust design
- Excellent HF safety
- **Equipment as delivered:**
- Collet body: Ø 2.4 mm

Accessories

SPOTARC TIG 18 W 5P 4m

094-500048-00000



- Spot welding torch, with welding nozzles for fillet welds, edge welds and flat welds incl. setting gauge
- Better surface formation in comparison to resistance welding
- Flatter spot formation in comparison to MAG spot welding
- Excellent seam quality due to minimal heat input
- Very low thermal stresses and little distortion due to short welding times
- Perfect for visible joints due to clean seam appearance
- Robust design
- Excellent HF safety
- **Equipment as delivered:**
- Collet body: Ø 2.4 mm

TIG 200 GRIP GD 5P 4m

394-510981-00600



- Gas-cooled TIG welding torch
- Double push-button
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 11 mm, size 7
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 200 GRIP GD 5P HFL 4m

394-510981-10600



- Gas cooled TIG welding torch with a highly flexible hose package
- Double push-button
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 11 mm, size 7
- Tungsten electrode E3 (purple): Ø 2.4 mm

Accessories

TIG 260 GRIP WD 5P 4m

394-510990-00600



- Water-cooled TIG welding torch
- Double push-button
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 10 mm, size 8
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 260 GRIP Little WD HFL 5P 4 m

394-510991-10600



- Water cooled TIG welding torch with a highly flexible hose package
- Double push-button
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 10 mm, size 8
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 260 GRIP WD 5P HFL 4m

394-510990-10600



- Water cooled TIG welding torch with a highly flexible hose package
- Double push-button
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 10 mm, size 8
- Tungsten electrode E3 (purple): Ø 2.4 mm

Accessories

TIG 200 GRIP GD 8P U/D 4m

394-510981-00200



- Gas-cooled TIG welding torch
- Setting of welding current and programs
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Suitable for devices from the Tetrix DC and AC/DC series
- An 8-pole connection socket is required for portable machines
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 11 mm, size 7
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 200 GRIP GD 8P U/D HFL 4m

394-510981-10200



- Gas cooled TIG welding torch with a highly flexible hose package
- Setting of welding current and programs
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Suitable for devices from the Tetrix DC and AC/DC series
- An 8-pole connection socket is required for portable machines
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 11 mm, size 7
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 260 GRIP WD 8P U/D 4m

394-510990-00200



- Water-cooled TIG welding torch
- Setting of welding current and programs
- Ergonomic GRIP handle for a secure grip
- Suitable for devices from the Tetrix DC and AC/DC series
- An 8-pole connection socket is required for portable machines
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 10 mm, size 8
- Tungsten electrode E3 (purple): Ø 2.4 mm

Accessories

TIG 260 GRIP WD 8P U/D HFL 4m

394-510990-10200



- Water cooled TIG welding torch with a highly flexible hose package
- Setting of welding current and programs
- Ergonomic GRIP handle for a secure hold and ergonomic use
- Suitable for devices from the Tetrix DC and AC/DC series
- An 8-pole connection socket is required for portable machines
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 10 mm, size 8
- Tungsten electrode E3 (purple): Ø 2.4 mm

TIG 260 WD GRIP 12P RETOX HFL 4m

394-510990-10700



- Water cooled TIG welding torch with a highly flexible hose package
- Setting and display of welding current and programs
- Ergonomic GRIP handle for a secure hold and ergonomic use
- For Tetrix DC, AC/DC Comfort and Synergic
- "ON 12-pole connection socket" option required
- Excellent HF safety
- **Equipment as delivered:**
- Electrode holder: Ø 2.4 mm
- Gas nozzle: Ø 10 mm, size 8
- Tungsten electrode E3 (purple): Ø 2.4 mm

ON LG-EX

090-008789-00502



- Networking via external LAN gateway for machines with 7-pole digital interface

ON WLG-EX

090-008790-00502



- Networking via external WiFi gateway for machines with 7-pole digital interface

Accessories

Trolley 35.2-2

090-008296-00000



- Transport cart
- Solid, stable design
- For transporting a power source, a cooling unit and a gas cylinder
- Can be lifted by crane (option ON CS Trolley 35.2-2 required)

Trolley 38-2 E

090-008270-00000



- Transport cart
- For Tetrix 230, 270, 300, 300-2, 400-2 DC as well as Tetrix 230, 300 AC/DC
- Solid, stable design
- For transporting a power source, a cooling unit and a gas cylinder
- Dimensions L x W x H in mm, 818 x 533 x 1233 Weight 35 kg

Trolley 55-5

090-008632-00000



- Transport cart
- Solid, stable design
- For transporting a power source, a cooling unit and a gas cylinder

RT50 7POL

090-008793-00000



- The RT50 7POL remote control allows machines with a 7-pole connection to be equipped with a second remote control
- Robust metal casing with rubber feet, retaining clip and holding magnet, 7-pole connection socket

Accessories

RT1 19POL

090-008097-00000



- Remote control, current
- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- Operating point setting directly at the site of welding
- Robust metal casing with rubber feet, retaining clip and holding magnet

RTG1 19POL 5m

090-008106-00000



- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- With pre-fitted 5 or 10 m connection cable
- Operating point setting directly at the site of welding
- For Tetrix, Picotig 200 AC/DC and Stick machine series

RTP1 19POL

090-008098-00000



- Remote control, pulse, spot and pause times are infinitely adjustable.
- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- Pulse/spot/normal
- Operating point setting directly at the site of welding
- Robust metal casing with rubber feet, retaining clip and holding magnet
- For Tetrix and Picotig 200 AC/DC machine series

RTP2 19POL

090-008099-00000



- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- Pulse/spot/normal
- Frequency and spot times infinitely adjustable.
- Coarse adjustment of the cycle frequency.
- Pulse/pause ratio (balance) adjustable from 10% to 90%.
- Operating point setting directly at the site of welding
- Robust metal casing with rubber feet, retaining clip and holding magnet
- For Tetrix and Picotig 200 AC/DC machine series

Accessories

RTP3 spotArc 19POL

090-008211-00000



- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- Remote control, pulse / spotArc spot welding / normal
- Frequency and spot times infinitely adjustable.
- Coarse adjustment of the cycle frequency.
- Pulse/pause ratio (balance) adjustable from 10% to 90%.
- Operating point setting directly at the site of welding
- Robust metal casing with rubber feet, retaining clip and holding magnet
- For Tetrix and Picotig 200 AC/DC machine series

RTF1 19POL 5 M

094-006680-00000



- Foot-operated remote control, start/stop
- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- Start/stop welding operation
- Operating point setting directly at the site of welding

RA5 19POL 20m

092-001470-00020



- Connection cables

ON 12pol TIG Tetrix 190/230

092-002519-00000



- 12-pole torch connection socket

WK25mm² 230A/60% 4m FIX

398-000593-00000



- Completely assembled workpiece lead with original FIX clamp

Accessories

WK70mm² 450A/60% 4m/Z
092-000013-00000



- Completely assembled workpiece lead with clamp

WK25mm² 230A/60% 4m/K
092-000016-00000



- Completely assembled workpiece lead with terminal

EH 35qmm 4m
092-000052-00000



- Fully assembled electrode holder with cable

ADAP 8-5 POL
092-000940-00000



- 8-to-5-pole cable adapter

ON AL D13/27
092-003282-00000



- Cap for load sockets

Gas hose
094-000010-00001



- Equipped with plastic nuts on both sides for tool-free assembly

Accessories

ON TH XX5 R

092-002699-00000



- Torch holder, right

L-BOXX 374

094-003899-00000



- Robuste Transportbox

L-BOXX 102

094-003900-00000



- Robuste Transportbox

KF 23E-10, -10

094-000530-00000



- Coolant (-10 °C), 9.3 l