

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Wall and ceiling sanders

WST 700 VV, without suction hose

Order no. 378.127**Vario-Giraffe® wall and ceiling sander**

- VV electronic control: controlled constant speed, soft-start, overload protection and speed selection with adjuster wheel
- Using a unique telescopic system, the Vario-Giraffe® adapts to your needs. Length adjustable from 1330 mm - 1730 mm. Open telescope lock lever, pull out handle and close lever. Handle rotates through 360°
- Adjustable locking screw for telescopic extension
- Ergonomic design with many different handling possibilities for fatigue-free working. The motor is always kept between the gripping positions, ensuring a perfect balance
- With round sanding head that can be exchanged with just a click
- Backing pad with hook and loop face
- Vacuum cleaning system: guard with a brush ring, flexible suction hose from the sanding head to the guide tube. Connection facility at the rear of the telescopic tube for FLEX safety vacuum cleaner
- The brush ring is spring-mounted so that the round sanding head accurately follows all uneven contours. This allows the head to be applied with fingertip precision and also prevents any dust escaping
- Effective dust extraction from between the brush ring and the sanding pad (round) and through the 10-hole extraction ports prevents clogging of the abrasive and promotes a healthy, dust-free working environment
- The articulating sanding head can be adjusted to every tilt and angle.
- Ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting, polishing
- This machine is also available in 110 V

Technical attributes	WST 700 VV, without suction hose
Power input	710 watt
Power output	420 watt
No load speed	1000-1500 rpm
Dimensions in mm	1330-1730
Weight	4,8 kg

Standard equipment	
Round sanding head with velcro sanding pad soft	350.346
Velcro backed abrasive paper, Select, 1 x P 60, 80, 100, 220	
1 hexagon socket screw key, special tool 5	
Carry case	