

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Wall and ceiling sanders

WST 700 VV, without suction hose

Order no. 378.127**Vario-Giraffe® wall and ceiling sander**

- VV electronic control: controlled constant speed, soft-start, overload protection and speed selection with adjuster wheel
- Using a unique telescopic system, the Vario-Giraffe® adapts to your needs. Length adjustable from 1330 mm - 1730 mm. Open telescope lock lever, pull out handle and close lever. Handle rotates through 360°
- Adjustable locking screw for telescopic extension
- Ergonomic design with many different handling possibilities for fatigue-free working. The motor is always kept between the gripping positions, ensuring a perfect balance
- With round sanding head that can be exchanged with just a click
- Backing pad with hook and loop face
- Vacuum cleaning system: guard with a brush ring, flexible suction hose from the sanding head to the guide tube. Connection facility at the rear of the telescopic tube for FLEX safety vacuum cleaner
- The brush ring is spring-mounted so that the round sanding head accurately follows all uneven contours. This allows the head to be applied with fingertip precision and also prevents any dust escaping
- Effective dust extraction from between the brush ring and the sanding pad (round) and through the 10-hole extraction ports prevents clogging of the abrasive and promotes a healthy, dust-free working environment
- The articulating sanding head can be adjusted to every tilt and angle.
- Ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting, polishing
- This machine is also available in 110 V

Technical attributes	WST 700 VV, without suction hose
Power input	710 watt
Power output	420 watt
No load speed	1000-1500 rpm
Dimensions in mm	1330-1730
Weight	4,8 kg

Standard equipment	
Round sanding head with velcro sanding pad soft	350.346
Velcro backed abrasive paper, Select, 1 x P 60, 80, 100, 220	
1 hexagon socket screw key, special tool 5	
Carry case	

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Wall and ceiling sanders

Accessories

Velcro sanding grid



For rapid removal of fine surface irregularities.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

225 Ø	grit 100	25	260.230
-------	----------	----	---------



For rapid removal of surface irregularities.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

225 Ø	grit 80	25	260.237
-------	---------	----	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Wall and ceiling sanders

Velcro abrasive paper, Select, round



For sanding joint filler in drywall construction, punched for dust extraction.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

225 Ø	P 16	10	350.079
-------	------	----	---------



For sanding joint filler in drywall construction, punched for dust extraction.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

225 Ø	P 40	20	370.924
-------	------	----	---------

225 Ø	P 60	25	348.503
-------	------	----	---------

225 Ø	P 80	25	348.511
-------	------	----	---------

225 Ø	P 100	25	348.538
-------	-------	----	---------

225 Ø	P 120	25	349.216
-------	-------	----	---------

225 Ø	P 150	25	349.224
-------	-------	----	---------

225 Ø	P 180	25	349.232
-------	-------	----	---------

225 Ø	P 220	25	348.546
-------	-------	----	---------

225 Ø	5x P 80/100/120/150/180	25	370.932
-------	----------------------------	----	---------

Carry case



Made of shock-resistant plastic for the WST and WSE 7 as well as for sanding tools and exchangeable heads.

QTY/PKG:	Order no.
----------	-----------

1	389.986
---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Wall and ceiling sanders

Round sanding head



Optimally suitable for finishing large surfaces on walls and ceilings.
Effective dust extraction, high surface removal rate.

QTY/PKG:	Order no.
----------	-----------

1	350.346
---	---------

Velcro backing pad Ø 225, round



Hard backing pad with high removal rate, with use with velcro backed abrasives.

Type:	QTY/PKG:	Order no.
-------	----------	-----------

hard	1	350.362
------	---	---------



Medium backing pad for sanding down soft fillers. Velcro system for fixing of abrasives.

Type:	QTY/PKG:	Order no.
-------	----------	-----------

medium	1	352.306
--------	---	---------



Soft. Highly flexible backing pad. Facilitates handling and allows for sensitive working. Prevents damage (swirl marks) when the pad touches the surface. For use with velcro backed abrasives.

Type:	QTY/PKG:	Order no.
-------	----------	-----------

soft	1	366.862
------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Wall and ceiling sanders

Storage system



Fits on to the industrial vacuum cleaner S 47, S 47 M, VCE 35 L AC, VCE 45 L AC, VCE 45 M AC, VCE 45 H AC for resting the WST 700 VV Giraffe®, WST 1000 FV or MS 1706 FR wall chaser and vacuum hose.

QTY/PKG:	Order no.
----------	-----------

1	350.370
---	---------

Antistatic suction hose



Antistatic suction hose Ø 32 mm x 4 m with snap coupling and coupling bush for vacuum cleaner incl. universal adapter (320.188) antistatic.

QTY/PKG:	Order no.
----------	-----------

1	354.953
---	---------

Clip adapter



For connecting a FLEX power tool to extraction units from other manufacturers. Suitable for hoses inside Ø 27 mm, outside Ø 36 mm.

QTY/PKG:	Diameter in mm:	Order no.
----------	-----------------	-----------

1	42/37	380.377
---	-------	---------