

Tetrix 401 Synergic FW

090-000179-00502



WE ARE WELDING



- Water-cooled DC TIG inverter welding machine with one-knob Synergic operation
- Features user database for Synergic operation at no extra charge
- Simple, menu-guided selection of welding tasks from user database
- 256 pre-programmed JOBS/characteristics in the user database
- Features characteristics for EWM activArc and EWM spotArc at no extra charge
- TIG welding with reproducible, electronic HF start
- TIG lift arc welding without HF
- Synergic or manual welding operation
- TIG automated pulsing with automatic specification of required pulse parameters
- Pulsed TIG welding in Hz and kHz range up to 15 kHz
- Large power reserves thanks to high duty cycle with all components heating up less as a result, guaranteeing a longer service life for machines when in use
- Non-latched/latched operation
- Reduced secondary current accessible using torch trigger
- Spot welding/tack function (spotArc/spotmatic)
- Up-slope/down-slope adjustable
- Spotmatic – halves time required for tacking
- Adjustable gas pre-flows/post-flows
- **MMA-Welding/gouging**
- MMA/gouging, automated pulsing with automatic specification of required pulse parameters
- Ideal for root welding
- Safe, reliable vertical-up and vertical-down welding
- Adjustable hot start current and hot start time
- Adjustable Arcforce
- Antistick function
- Excellent torch cooling, resulting in cost savings on consumables due to high-performance centrifugal pump and 12-litre water tank
- Energy-saving thanks to high efficiency and standby function
- Connection capability for remote control and function torch
- Crane-liftable casing
- Can be optionally networked with LAN or WiFi and EWM Xnet software

	TIG		MMA
Setting range for welding current	5 A - 400 A		
Duty cycle at ambient t.e	40 °C	25 °C	40 °C
100 %	400 A		–
Open circuit voltage	80 V , 79 V		
Mains frequency	50 Hz / 60 Hz		
Mains fuses (slow-blow)	3 x 32 A		
Mains voltage (tolerances)	3 x 400 V (-25 % - +20 %)		
Max. connected load	13.5 kVA		18.5 kVA
Recommended generator power	18.2 kVA		25 kVA
cos φ	0.99		
Efficiency	90 %		
Dimensions machine, LxWxH in mm	1100 x 455 x 1000		
Weight, machine	126 kg		
Torch connection	Decentral		

28.06.2018