

Tetrix XQ 230 puls DC Expert 3.0 8P

090-005630-00004



- Modular DC TIG inverter welding machine of the latest generation
- TIG DC and TIG pulse
- activArc® and spotArc®
- MMA, MMA pulse, MMA cel, MMA cel pulse
- Machine configuration ex works:
- Expert 3.0 control with 7" high-resolution graphic display (no touchscreen) with plain text display for selecting all parameters and control customisation
- Robust housing with impact-resistant plastic cover
- Provided ex works ready for water block connection – guarantees ultimate flexibility in industry and trade
- Splash-proof in line with IP23
- Temperature- and speed-controlled cooling fan – reduced contamination and less noise emissions as fan only runs when needed
- Generator-compatible, even with long mains leads
- High mains voltage tolerance
- Consumables box in the handle – consumables always safely stored and within reach
- LED status bar indicates the current operating status with colours
- 3.5 m mains lead with 16 A earthed plug

| | |
|-----------------------------------|---|
| Version | Tetrix XQ 230 puls DC EX3 8POL |
| Setting range for welding current | 3 A - 230 A |
| Duty cycle 40 °C | 230 A / 45 % |
| | 205 A / 60 % |
| | 170 A / 100 % |
| Open circuit voltage | 96 V |
| Mains voltage | 1 x 230 V |
| Tolerances | -40 % up to +15 % |
| Mains frequency | 50 Hz / 60 Hz |
| Recommended generator power | 6.9 kVA |
| Protection classification | IP23 |
| Safety marking |  |
| EMC class | A |
| Dimensions (L x B x H) | 550 mm x 224 mm x 415 mm |
| | 21.7 inch x 8.8 inch x 16.3 inch |
| Weight | 17.5 kg |
| | 38.6 lbs |
| Standards | IEC 60974-1, -3 and -10 CL.A |