

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Saws

CSM 4060

Order no. 307.815**Metal-cutting circular saw for dry cutting**

- For accurate metal cutting without coolant
- Tool-free adjustable guide plate, continuous saw depth adjustment to 63 mm
- Chip collection compartment with sight glass: large capacity, tool-free emptying
- Special carbide-tipped saw blades: nearly burr-free cuts, trimming threaded bars possible without recutting the thread
- Spindle lock
- Switch: with lock-off / lock-on switch
- Solid material / flat steel: 6 mm; -Round material: 20 mm; - Hollow sections: 63 mm

| Technical attributes | CSM 4060 |
|--|-----------|
| Blade Ø | 185 mm |
| Saw blade drill Ø | 20 mm |
| Max. cutting depth (90°) | 0-63 mm |
| Max. material thickness in steel 400 N/mm ² | 6 mm |
| Max. material thickness in aluminium 250 N/mm ² | 10 mm |
| No load speed | 3800 rpm |
| Power input | 1400 watt |
| Power output | 720 watt |
| Weight | 5,4 kg |

| Standard equipment | |
|---|--------------|
| 2 carbide tipped saw blades for steel, 38 teeth (185 x 20 mm) | 312.304 (2x) |
| 1 parallel guide fence | 312.312 |
| 1 ring / open-ended wrench | 312.347 |
| 1 plastic carry case | 1 piece |