

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Saws

### CSM 4060

Order no. 307.815

**Metal-cutting circular saw for dry cutting**

- For accurate metal cutting without coolant
- Tool-free adjustable guide plate, continuous saw depth adjustment to 63 mm
- Chip collection compartment with sight glass: large capacity, tool-free emptying
- Special carbide-tipped saw blades: nearly burr-free cuts, trimming threaded bars possible without recutting the thread
- Spindle lock
- Switch: with lock-off / lock-on switch
- Solid material / flat steel: 6 mm; -Round material: 20 mm; - Hollow sections: 63 mm

**Accessories****Carbide tipped saw blade for steel**

Enables a practically burr-free cut, no touching up is necessary.

Dimensions in mm:	Teeth:	QTY/PKG:	Order no.
----------------------	--------	----------	-----------

185 Ø x 20	38	1	312.304
------------	----	---	---------

Technical attributes	CSM 4060
Blade Ø	185 mm
Saw blade drill Ø	20 mm
Max. cutting depth (90°)	0-63 mm
Max. material thickness in steel 400 N/mm <sup>2</sup>	6 mm
Max. material thickness in aluminium 250 N/mm <sup>2</sup>	10 mm
No load speed	3800 rpm
Power input	1400 watt
Power output	720 watt
Weight	5,4 kg

Standard equipment	
2 carbide tipped saw blades for steel, 38 teeth (185 x 20 mm)	312.304 (2x)
1 parallel guide fence	312.312
1 ring / open-ended wrench	312.347
1 plastic carry case	1 piece