

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Wall and ceiling sanders

### WST 700 VV Plus, without suction hose

Order no. 374.547



#### Vario-Giraffe® wall and ceiling sander

- VV electronic control: controlled constant speed, soft-start, overload protection and speed selection with adjuster wheel
- Using a unique telescopic system, the Vario-Giraffe® adapts to your needs. Length adjustable from 1330 mm - 1730 mm. Open telescope lock lever, pull out handle and close lever. Handle rotates through 360°
- Adjustable locking screw for telescopic extension
- Ergonomic design with many different handling possibilities for fatigue-free working. The motor is always kept between the gripping positions, ensuring a perfect balance
- Fitted with interchangeable heads that are attached and removed with a click.
- Including triangular sanding head. This is optimally suited to sanding corners and edges. The random orbital movement of the sanding head takes the abrasive right up to the edges
- Backing pad with hook and loop face
- The articulating sanding head can be adjusted to every tilt and angle.
- Vacuum cleaning system: guard with a brush ring, flexible suction hose from the sanding head to the guide tube. Connection facility at the rear of the telescopic tube for FLEX safety vacuum cleaner
- Effective dust extraction from between the brush ring and the sanding pad (round) and through the 10-hole extraction ports prevents clogging of the abrasive and promotes a healthy, dust-free working environment
- The brush ring is spring-mounted so that the round sanding head accurately follows all uneven contours. This allows the head to be applied with fingertip precision and also prevents any dust escaping
- Ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting, polishing

Technical attributes	WST 700 VV Plus, without suction hose
Power input	710 watt
Power output	420 watt
No load speed	1000-1500 rpm
Corner sander no-load speed	3000-4500 rpm
Dimensions in mm	1330-1730
Weight	4,8 kg

Standard equipment	
Triangular sanding head	388.289
Round sanding head with velcro sanding pad soft	350.346
Velcro backed abrasive paper, Select, 1 x P 60, 80, 100, 220	
Velcro backed abrasive paper, triangular, Select, 1 x P 60, 80, 100, 220	
1 hexagon socket screw key, special tool 5	
Carry case	