

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Wall and ceiling sanders

### WST 700 VV Plus, without suction hose

**Order no. 374.547****Vario-Giraffe® wall and ceiling sander**

- VV electronic control: controlled constant speed, soft-start, overload protection and speed selection with adjuster wheel
- Using a unique telescopic system, the Vario-Giraffe® adapts to your needs. Length adjustable from 1330 mm - 1730 mm. Open telescope lock lever, pull out handle and close lever. Handle rotates through 360°
- Adjustable locking screw for telescopic extension
- Ergonomic design with many different handling possibilities for fatigue-free working. The motor is always kept between the gripping positions, ensuring a perfect balance
- Fitted with interchangeable heads that are attached and removed with a click.
- Including triangular sanding head. This is optimally suited to sanding corners and edges. The random orbital movement of the sanding head takes the abrasive right up to the edges
- Backing pad with hook and loop face
- The articulating sanding head can be adjusted to every tilt and angle.
- Vacuum cleaning system: guard with a brush ring, flexible suction hose from the sanding head to the guide tube. Connection facility at the rear of the telescopic tube for FLEX safety vacuum cleaner
- Effective dust extraction from between the brush ring and the sanding pad (round) and through the 10-hole extraction ports prevents clogging of the abrasive and promotes a healthy, dust-free working environment
- The brush ring is spring-mounted so that the round sanding head accurately follows all uneven contours. This allows the head to be applied with fingertip precision and also prevents any dust escaping
- Ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting, polishing

Technical attributes	WST 700 VV Plus, without suction hose
Power input	710 watt
Power output	420 watt
No load speed	1000-1500 rpm
Corner sander no-load speed	3000-4500 rpm
Dimensions in mm	1330-1730
Weight	4,8 kg

Standard equipment	
Triangular sanding head	388.289
Round sanding head with velcro sanding pad soft	350.346
Velcro backed abrasive paper, Select, 1 x P 60, 80, 100, 220	
Velcro backed abrasive paper, triangular, Select, 1 x P 60, 80, 100, 220	
1 hexagon socket screw key, special tool 5	
Carry case	

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Wall and ceiling sanders

### Accessories

#### Velcro sanding grid



For rapid removal of fine surface irregularities.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

225 Ø	grit 100	25	260.230
-------	----------	----	---------



For rapid removal of surface irregularities.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

225 Ø	grit 80	25	260.237
-------	---------	----	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Wall and ceiling sanders

### Velcro abrasive paper, Select, round



For sanding joint filler in drywall construction, punched for dust extraction.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

225 Ø	P 16	10	350.079
-------	------	----	---------



For sanding joint filler in drywall construction, punched for dust extraction.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

225 Ø	P 40	20	370.924
-------	------	----	---------

225 Ø	P 60	25	348.503
-------	------	----	---------

225 Ø	P 80	25	348.511
-------	------	----	---------

225 Ø	P 100	25	348.538
-------	-------	----	---------

225 Ø	P 120	25	349.216
-------	-------	----	---------

225 Ø	P 150	25	349.224
-------	-------	----	---------

225 Ø	P 180	25	349.232
-------	-------	----	---------

225 Ø	P 220	25	348.546
-------	-------	----	---------

225 Ø	5x P 80/100/120/150/180	25	370.932
-------	----------------------------	----	---------

### Triangular sanding head



Ideally suited for the processing of corners and edges. The eccentric movement of the sanding head guides the sanding tool directly up to the edge. With exchangeable protective corners with sliding strips.

QTY/PKG:	Order no.
----------	-----------

1	388.289
---	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Wall and ceiling sanders

### Carry case



Made of shock-resistant plastic for the WST and WSE 7 as well as for sanding tools and exchangeable heads.

QTY/PKG:	Order no.
----------	-----------

1	389.986
---	---------

### Velcro abrasive paper Select, triangular



For sanding joint filler in drywall construction, punched for dust extraction.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

290	P 16	10	350.095
-----	------	----	---------



For sanding joint filler in drywall construction, punched for dust extraction.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

290	P 40	20	370.940
290	P 60	25	348.554
290	P 80	25	348.562
290	P 100	25	348.570
290	P 120	25	349.240
290	P 150	25	349.259
290	P 180	25	349.267
290	P 220	25	348.589
290	5x P 80/100/120/150/180	25	370.959

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Wall and ceiling sanders

### Round sanding head



Optimally suitable for finishing large surfaces on walls and ceilings.  
Effective dust extraction, high surface removal rate.

QTY/PKG:	Order no.
----------	-----------

1	350.346
---	---------

### Velcro backing pad Ø 225, round



Hard backing pad with high removal rate, with use with velcro backed abrasives.

Type:	QTY/PKG:	Order no.
-------	----------	-----------

hard	1	350.362
------	---	---------



Medium backing pad for sanding down soft fillers. Velcro system for fixing of abrasives.

Type:	QTY/PKG:	Order no.
-------	----------	-----------

medium	1	352.306
--------	---	---------



Soft. Highly flexible backing pad. Facilitates handling and allows for sensitive working. Prevents damage (swirl marks) when the pad touches the surface. For use with velcro backed abrasives.

Type:	QTY/PKG:	Order no.
-------	----------	-----------

soft	1	366.862
------	---	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Wall and ceiling sanders

### Velcro triangular backing pad



Backing pad for plaster or hard filler compounds in drywall construction, for use with velcro backed abrasives.

QTY/PKG:	Order no.
----------	-----------

1	354.988
---	---------

### Storage system



Fits on to the industrial vacuum cleaner S 47, S 47 M, VCE 35 L AC, VCE 45 L AC, VCE 45 M AC, VCE 45 H AC for resting the WST 700 VV Giraffe®, WST 1000 FV or MS 1706 FR wall chaser and vacuum hose.

QTY/PKG:	Order no.
----------	-----------

1	350.370
---	---------

### Antistatic suction hose



Antistatic suction hose Ø 32 mm x 4 m with snap coupling and coupling bush for vacuum cleaner incl. universal adapter (320.188) antistatic.

QTY/PKG:	Order no.
----------	-----------

1	354.953
---	---------

### Clip adapter



For connecting a FLEX power tool to extraction units from other manufacturers. Suitable for hoses inside Ø 27 mm, outside Ø 36 mm.

QTY/PKG:	Diameter in mm:	Order no.
----------	-----------------	-----------

1	42/37	380.377
---	-------	---------