

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Wall and ceiling sanders

### WST 700 VV Plus

**Order no. 350.338****Vario-Giraffe® wall and ceiling sander**

- VV electronic control: controlled constant speed, soft-start, overload protection and speed selection with adjuster wheel
- Using a unique telescopic system, the Vario-Giraffe® adapts to your needs. Length adjustable from 1330 mm - 1730 mm. Open telescope lock lever, pull out handle and close lever. Handle rotates through 360°
- Adjustable locking screw for telescopic extension
- Ergonomic design with many different handling possibilities for fatigue-free working. The motor is always kept between the gripping positions, ensuring a perfect balance
- Fitted with interchangeable heads that are attached and removed with a click.
- Including triangular sanding head. This is optimally suited to sanding corners and edges. The random orbital movement of the sanding head takes the abrasive right up to the edges
- Backing pad with hook and loop face
- The articulating sanding head can be adjusted to every tilt and angle.
- Vacuum cleaning system: guard with a brush ring, flexible suction hose from the sanding head to the guide tube. Connection facility at the rear of the telescopic tube for FLEX safety vacuum cleaner
- Effective dust extraction from between the brush ring and the sanding pad (round) and through the 10-hole extraction ports prevents clogging of the abrasive and promotes a healthy, dust-free working environment
- The brush ring is spring-mounted so that the round sanding head accurately follows all uneven contours. This allows the head to be applied with fingertip precision and also prevents any dust escaping
- Ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting, polishing
- This machine is also available in 110 V

| Technical attributes        | WST 700 VV Plus |
|-----------------------------|-----------------|
| Power input                 | 710 watt        |
| Power output                | 420 watt        |
| No load speed               | 1000-1500 rpm   |
| Corner sander no-load speed | 3000-4500 rpm   |
| Dimensions in mm            | 1330-1730       |
| Weight                      | 4,8 kg          |

| Standard equipment  |                     |
|---|---------------------|
| Triangular sanding head   | 388.289             |
| Round sanding head with velcro sanding pad soft   | 350.346             |
| Velcro backed abrasive paper, Select, 1 x P 60, 80, 100, 220                                  |                     |
| Velcro backed abrasive paper, triangular, Select, 1 x P 60, 80, 100, 220                      | 1 item from 348.570 |
| 1 hexagon socket screw key, special tool 5  |                     |
| Antistatic suction hose 32 mm Ø x 4 m with snap coupling and coupling bush for vacuum cleaner | 354.953             |
| Carry case  | 1 piece             |

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Wall and ceiling sanders

### Accessories

#### Velcro abrasive paper, Select, round



For sanding joint filler in drywall construction, punched for dust extraction.

| Dimensions<br>in mm: | Grit: | QTY/PKG: | Order no. |
|----------------------|-------|----------|-----------|
|----------------------|-------|----------|-----------|

|       |      |    |         |
|-------|------|----|---------|
| 225 Ø | P 16 | 10 | 350.079 |
|-------|------|----|---------|



For sanding joint filler in drywall construction, punched for dust extraction.

| Dimensions<br>in mm: | Grit: | QTY/PKG: | Order no. |
|----------------------|-------|----------|-----------|
|----------------------|-------|----------|-----------|

|       |                            |    |         |
|-------|----------------------------|----|---------|
| 225 Ø | P 40                       | 20 | 370.924 |
| 225 Ø | P 60                       | 25 | 348.503 |
| 225 Ø | P 80                       | 25 | 348.511 |
| 225 Ø | P 100                      | 25 | 348.538 |
| 225 Ø | P 120                      | 25 | 349.216 |
| 225 Ø | P 150                      | 25 | 349.224 |
| 225 Ø | P 180                      | 25 | 349.232 |
| 225 Ø | P 220                      | 25 | 348.546 |
| 225 Ø | 5x P<br>80/100/120/150/180 | 25 | 370.932 |

#### Triangular sanding head



Ideally suited for the processing of corners and edges. The eccentric movement of the sanding head guides the sanding tool directly up to the edge. With exchangeable protective corners with sliding strips.

| QTY/PKG: | Order no. |
|----------|-----------|
|----------|-----------|

|   |         |
|---|---------|
| 1 | 388.289 |
|---|---------|

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Wall and ceiling sanders

### Carry case



Made of shock-resistant plastic for the WST and WSE 7 as well as for sanding tools and exchangeable heads.

| QTY/PKG: | Order no. |
|----------|-----------|
|----------|-----------|

|   |         |
|---|---------|
| 1 | 389.986 |
|---|---------|

### Velcro sanding grid



For rapid removal of fine surface irregularities.

| Dimensions<br>in mm: | Grit: | QTY/PKG: | Order no. |
|----------------------|-------|----------|-----------|
|----------------------|-------|----------|-----------|

|       |          |    |         |
|-------|----------|----|---------|
| 225 Ø | grit 100 | 25 | 260.230 |
|-------|----------|----|---------|



For rapid removal of surface irregularities.

| Dimensions<br>in mm: | Grit: | QTY/PKG: | Order no. |
|----------------------|-------|----------|-----------|
|----------------------|-------|----------|-----------|

|       |         |    |         |
|-------|---------|----|---------|
| 225 Ø | grit 80 | 25 | 260.237 |
|-------|---------|----|---------|

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Wall and ceiling sanders

### Velcro abrasive paper Select, triangular



For sanding joint filler in drywall construction, punched for dust extraction.

| Dimensions<br>in mm: | Grit: | QTY/PKG: | Order no. |
|----------------------|-------|----------|-----------|
|----------------------|-------|----------|-----------|

|     |      |    |         |
|-----|------|----|---------|
| 290 | P 16 | 10 | 350.095 |
|-----|------|----|---------|



For sanding joint filler in drywall construction, punched for dust extraction.

| Dimensions<br>in mm: | Grit: | QTY/PKG: | Order no. |
|----------------------|-------|----------|-----------|
|----------------------|-------|----------|-----------|

|     |      |    |         |
|-----|------|----|---------|
| 290 | P 40 | 20 | 370.940 |
|-----|------|----|---------|

|     |      |    |         |
|-----|------|----|---------|
| 290 | P 60 | 25 | 348.554 |
|-----|------|----|---------|

|     |      |    |         |
|-----|------|----|---------|
| 290 | P 80 | 25 | 348.562 |
|-----|------|----|---------|

|     |       |    |         |
|-----|-------|----|---------|
| 290 | P 100 | 25 | 348.570 |
|-----|-------|----|---------|

|     |       |    |         |
|-----|-------|----|---------|
| 290 | P 120 | 25 | 349.240 |
|-----|-------|----|---------|

|     |       |    |         |
|-----|-------|----|---------|
| 290 | P 150 | 25 | 349.259 |
|-----|-------|----|---------|

|     |       |    |         |
|-----|-------|----|---------|
| 290 | P 180 | 25 | 349.267 |
|-----|-------|----|---------|

|     |       |    |         |
|-----|-------|----|---------|
| 290 | P 220 | 25 | 348.589 |
|-----|-------|----|---------|

|     |                            |    |         |
|-----|----------------------------|----|---------|
| 290 | 5x P<br>80/100/120/150/180 | 25 | 370.959 |
|-----|----------------------------|----|---------|

### Round sanding head



Optimally suitable for finishing large surfaces on walls and ceilings.  
Effective dust extraction, high surface removal rate.

| QTY/PKG: | Order no. |
|----------|-----------|
|----------|-----------|

|   |         |
|---|---------|
| 1 | 350.346 |
|---|---------|

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Wall and ceiling sanders

### Velcro backing pad Ø 225, round



Hard backing pad with high removal rate, with use with velcro backed abrasives.

| Type: | QTY/PKG: | Order no. |
|-------|----------|-----------|
| hard  | 1        | 350.362   |



Medium backing pad for sanding down soft fillers. Velcro system for fixing of abrasives.

| Type:  | QTY/PKG: | Order no. |
|--------|----------|-----------|
| medium | 1        | 352.306   |



Soft. Highly flexible backing pad. Facilitates handling and allows for sensitive working. Prevents damage (swirl marks) when the pad touches the surface. For use with velcro backed abrasives.

| Type: | QTY/PKG: | Order no. |
|-------|----------|-----------|
| soft  | 1        | 366.862   |

### Velcro triangular backing pad



Backing pad for plaster or hard filler compounds in drywall construction, for use with velcro backed abrasives.

| QTY/PKG: | Order no. |
|----------|-----------|
| 1        | 354.988   |

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Wall and ceiling sanders

### Storage system

---



Fits on to the industrial vacuum cleaner S 47, S 47 M, VCE 35 L AC, VCE 45 L AC, VCE 45 M AC, VCE 45 H AC for resting the WST 700 VV Giraffe®, WST 1000 FV or MS 1706 FR wall chaser and vacuum hose.

| QTY/PKG: | Order no. |
|----------|-----------|
|----------|-----------|

---

|   |         |
|---|---------|
| 1 | 350.370 |
|---|---------|

### Antistatic suction hose

---



Antistatic suction hose Ø 32 mm x 4 m with snap coupling and coupling bush for vacuum cleaner incl. universal adapter (320.188) antistatic.

| QTY/PKG: | Order no. |
|----------|-----------|
|----------|-----------|

---

|   |         |
|---|---------|
| 1 | 354.953 |
|---|---------|

### Clip adapter

---



For connecting a FLEX power tool to extraction units from other manufacturers. Suitable for hoses inside Ø 27 mm, outside Ø 36 mm.

| QTY/PKG: | Diameter in mm: | Order no. |
|----------|-----------------|-----------|
|----------|-----------------|-----------|

---

|   |       |         |
|---|-------|---------|
| 1 | 42/37 | 380.377 |
|---|-------|---------|