

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Metal surface finishing

### BRE 14-3 125 Set

Order no. 433.446



Technical attributes	BRE 14-3 125 Set
Power input	1400 watt
Power output	880 watt
Belt speed	3,5-10 m/sec
Belt dimensions	760 x 40 mm
Pipe Ø max.	125 mm
Cable length	4,0 m
Weight	3,6 kg

#### Pipe belt grinder TRINOXFLEX in set

- Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing and pipe belt sanding
- Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- Sanding belt replacement: quick and tool-free
- Sanding belt dimension: 760 x 40 mm
- High-quality, spring-mounted sanding arm: light alloy with 2 deflection rollers. For optimum wrap-round on pipes, up to max. 270°
- Single-pole switch
- Spindle lock

Standard equipment	
1 grinding attachment, pipe belt BR 125	433.470
1 sanding-polishing belt S 600	326.917
1 superfinishing band S 1500	326.933
1 sanding belt MESHFLEX A 240	1 piece of 326.879
1 sanding belt MESHFLEX A 400	1 piece of 326.852
5 sanding belts CORUFLEX P 80	5 pieces of 326.739
5 sanding belts CORUFLEX P 120	5 pieces of 326.755
5 sanding belts CORUFLEX P 220	5 pieces of 326.771
1 carrying case L-BOXX® 238	414.093
1 case insert	433.918