

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Metal surface finishing

BRE 14-3 125 Set

Order no. 433.446



Technical attributes	BRE 14-3 125 Set
Power input	1400 watt
Power output	880 watt
Belt speed	3,5-10 m/sec
Belt dimensions	760 x 40 mm
Pipe Ø max.	125 mm
Cable length	4,0 m
Weight	3,6 kg

Pipe belt grinder TRINOXFLEX in set

- Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing and pipe belt sanding
- Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- Sanding belt replacement: quick and tool-free
- Sanding belt dimension: 760 x 40 mm
- High-quality, spring-mounted sanding arm: light alloy with 2 deflection rollers. For optimum wrap-round on pipes, up to max. 270°
- Single-pole switch
- Spindle lock

Standard equipment	
1 grinding attachment, pipe belt BR 125	433.470
1 sanding-polishing belt S 600	326.917
1 superfinishing band S 1500	326.933
1 sanding belt MESHFLEX A 1 piece of 240	326.879
1 sanding belt MESHFLEX A 1 piece of 400	326.852
5 sanding belts CORUFLEX P 80	5 pieces of 326.739
5 sanding belts CORUFLEX P 120	5 pieces of 326.755
5 sanding belts CORUFLEX P 220	5 pieces of 326.771
1 carrying case L-BOXX® 238	414.093
1 case insert	433.918

Accessories

Grinding attachment, burnishing



Grinding attachment with integrated handle for burnishing. For the TRINOXFLEX. Tool-free fitting via the quick-change system.

QTY/PKG: Order no.**1 433.462**

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Metal surface finishing

Sanding belt ZIRCOFLEX



Grinding belt with high-quality, self-sharpening zirconium corundum for a longer service life. High abrasion performance in coarse and intermediate grinding on steel and stainless steel surfaces.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
760 x 40	P 36	10	438.464
760 x 40	P 40	10	438.472
760 x 40	P 60	10	438.480
760 x 40	P 80	10	438.499
760 x 40	P 120	10	438.502

Sanding belt CERAFLEX



Flexible high-performance grinding belt for optimum grinding performance, with high abrasion performance and an extremely long service life thanks to self-sharpening, micro-crystalline ceramic grit for preliminary and intermediate grinding on stainless steel surfaces. Cool grinding thanks to additional multi-bonding.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
760 x 40	60	10	438.510
760 x 40	80	10	438.529
760 x 40	120	10	438.537

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Metal surface finishing

Sanding belt CORUFLEX



Highly flexible grinding belt with annealed corundum grit and active-grinding agents for finishing stainless steel. Particularly suitable for finish grinding.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

760 x 40	P 80	10	326.739
----------	------	----	---------

760 x 40	P 120	10	326.755
----------	-------	----	---------

760 x 40	P 180	10	434.906
----------	-------	----	---------

760 x 40	P 240	10	434.914
----------	-------	----	---------

Sanding belt MESHFLEX



For removing minor damage, scratches, tarnish, flash rust, scale and dirt. Removing tarnish at welds without heat distortion at thin plates. For grinding, cleaning and finishing stainless steel, steel, titanium alloys, light metals, non-ferrous metals and plastics.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

760 x 40	A 100	3	326.895
----------	-------	---	---------

760 x 40	A 240	3	326.879
----------	-------	---	---------

760 x 40	A 400	3	326.852
----------	-------	---	---------

Superfinishing band



For high-gloss polishing without polishing agents in two steps.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

760 x 40	S 600	1	326.917
----------	-------	---	---------

760 x 40	S 1500	1	326.933
----------	--------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Metal surface finishing

Case insert

Matching insert for BSE/BRE/BSE INOX 14-3 for carry case L-BOXX® 238.

QTY/PKG:	Order no.
----------	-----------

1	433.918
---	---------

Carrying case L-BOXX®



The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXX®es optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert.

External dimensions L x W x H:	Internal dimensions L x W x H:	Weight:	QTY/PKG:	Order no.
442 x 357 x 253	378 x 306 x 209	2,8	1	414.093