FLEX-Elektrowerkzeuge GmbH Bahnhofstraße 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Cordless circular saw with pendulum hood 18,0 V

CS 62 18.0-EC/5.0 Set





Cordless circular saw with pendulum hood 18,0 V

- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + 18.0 V EC motor with overload protection and temperature monitoring
- + LED battery capacity display
- + Dual clamped swivel element prevents the saw blade from jamming when making mitre cuts and therefore the risk of recoil
- + Spindle lock: for quick replacement of blades
- + Angle scale from 0 $^{\circ}$ to 50 $^{\circ}$. With preset angles of 22.5 $^{\circ}$ / 45 $^{\circ}$, and 50 $^{\circ}$. Easy to read, precision adjustment via non-slip clamping elements
- + Swivel range from -1° to 50° for undercuts as well as scoring function for perfect visible edges
- + Intuitive clamp lever for cutting depth adjustment, cutting depth is easy to read off
- + In accordance with the latest regulations without splitting wedge for plunge cuts and without time-consuming removal of splitting wedge
- + Woodshaving collection bag for low-dust operation, simple to empty, tool-free attachment by means of bayonet connection
- + Connector for external dust extraction Ø 27 mm or step adapter
- + Ideal for traditional applications in dry construction and refurbishing, e.g. for making saw cuts through plasterboard, concrete fibre boards, wood materials, such as chipboard or OSB boards

Technical attributes	
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
No load speed	5000 rpm
Pivoting range	0-50 °
Saw blade holder	20 mm
Cutting depth	0-62 mm
Depth of cut - mitre cut	0-38 mm
Depth of cut - mitre cut with guide rail	0-32 mm
Blade Ø	165 mm
Angle preset	0°/22,5°/45°/ 50°
Size (WxLxH)	335 x 190 x 210 mm
Weight without battery	3,1 kg

Standard equipment	
1 saw blade Z 24-WZ	456.012
1 dust bag	1 piece
1 extraction adapter	1 piece
2 batteries 5.0 Ah AP 18.0/5.0	445.894
1 charger CA 10.8/18.0	417.882
1 carrying case L-BOXX [®] 374	414.107
1 case insert	459.380