

FLEX-Elektrowerkzeuge GmbH
 Bahnhofstraße 15
 71711 Steinheim
 Phone +49 7144 828-0
 Fax +49 7144 25899
 info@flex-tools.com
 www.flex-tools.com

FLEX
 Das Original

Belt file TRINOXFLEX

FBE 8-4 140

Order number 453.455



Belt file TRINOXFLEX

- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Highly efficient and resilient motor for more power output
- + VE electronic control: for infinitely adjustable belt speed
- + Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing, pipe belt sanding, filing
- + Sanding head: rotates through 140°. For use with sanding arms in 9 mm or 30 mm
- + Sanding arm adjustable for 520 mm and 533 mm belt lengths
- + Processing length sanding arm up to approx. 12 cm
- + Quick belt replacement system: for quick, tool-free belt replacement

Technical attributes

Power input	800 watt
Power output	325 watt
Belt speed	2,8-8,4 m/sec
Belt dimensions	533 x 4-9 / 4-30 mm
Cable length	4,0 m
Weight	2,5 kg

Standard equipment

1 sanding attachment belt file BF 140	459.593
2 sanding belts ZIRCOFLEX P 60, 4 mm	2 pieces of 303.615
2 sanding belts ZIRCOFLEX, P 120, 4 mm	2 pieces of 303.623
2 sanding belts ZIRCOFLEX, P 60, 9 mm	2 pieces of 257.105
2 sanding belts ZIRCOFLEX, P 120, 9 mm	2 pieces of 257.102
2 sanding belts ZIRCOFLEX, P 60, 30 mm	2 pieces of 255.328
2 sanding belts ZIRCOFLEX, P 120, 30 mm	2 pieces of 255.329
1 sanding belt MESHFLEX A 240, 9 mm	1 piece of 318.663
1 sanding belt MESHFLEX A 240, 30 mm	1 piece of 318.647
1 side handle	194.034
1 hexagon socket wrench, SW 5	115.460
1 carrying case L-BOXX® 136	414.085
1 case insert	457.337