

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Surface finishing sanding, rotary

LL 1107 VEA

Order no. 289.434

Technical attributes	LL 1107 VEA
Power input	710 watt
Power output	420 watt
No load speed	700-2300 rpm
Max. disc diameter	115 mm
Sanding head level	13 mm
Weight	2,7 kg

Flounder 710 watt flat-head sander

- VE electronic control: with infinitely adjustable speed control
- Ideally suited to confined spaces from 15 mm gap width, e.g. window shutters, that are inaccessible with conventional grinders
- Handy, lightweight design
- Special accessory: metal carrying case (order no. 303.224)

Standard equipment	
1 side handle	194.034
Sand paper P 40, 115 Ø	1 piece of 381.209
Sand paper P 80, 115 Ø	1 piece of 381.225
Sand paper P 120, 115 Ø	1 piece of 381.241
1 velcro velours with foam coating 80 mm Ø	296.155

Accessories

Velcro sanding paper PURFLEX



Ideally suited to working wood and metal.

Dimensions **Grit:** **QTY/PKG:** **Order no.**
in mm:

115 Ø	P 24	25	381.195
115 Ø	P 40	50	381.209
115 Ø	P 60	50	381.217
115 Ø	P 80	50	381.225
115 Ø	P 100	50	381.233
115 Ø	P 120	50	381.241
115 Ø	P 150	50	381.268
115 Ø	P 180	50	381.276

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Surface finishing sanding, rotary

Velcro velours



With foam coating.

Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

80 Ø	1	296.155
------	---	---------