

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

L 10-10 125

Order no. 385.123**1010 watt angle grinder, 125 mm**

- Motor: powerful, strong motor for quick working progress
- 3-fold winding protection from dust. Reduces motor wear, increases service life. Protective guard on the winding end of the armature and plated winding on the armature.
- Epoxy-coated winding on the field coil
- Tool-free adjustment of guard. Extremely robust protection against bursting discs
- Compact, ergonomic design - snug fit in the hand
- Side handgrip
- Spindle lock

Technical attributes	L 10-10 125
Max. disc diameter	125 mm
No load speed	10000 rpm
Power input	1010 watt
Power output	600 watt
Tool fixture	M 14
Clamping neck Ø	40,3 mm
Size (W x L x H)	290 x 80 x 110 mm
Weight	2,2 kg

Standard equipment	
1 guard grinding	385.395
1 handle	335.274
1 pin wrench	100.100
1 clamping flange	335.282
1 clamping nut M14	100.080

Accessories**Side handgrip**

Handle for angle grinder, thread M10.

QTY/PKG: Order no.**1 335.274****Clamping flange**

Clamping flange for angle grinder, bore D 22.2 mm.

QTY/PKG: Order no.**1 335.282**

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

Clamping nut M 14



For use with flap sanding discs Ø 125 mm.

QTY/PKG: **Order no.****1** **100.080**

Face pin spanner

QTY/PKG: **Order no.****1** **100.110**

Carry case



Without insert. For the machines L 3709, LE 9-10 125, L 10-10 125 select insert no. 378.305. For the machines OS/OSE 80-2, OD/ODE 100-2, ORE 125-2 select insert no. 379.387.

Size (W x L x QTY/PKG: **Order no.****H):****360 x 228 x** **1** **376.094**
135

Case insert

Matching insert for carry case 376.094. For angle grinders L 3709, L 10-10 125 and LE 9-10 125.

QTY/PKG: **Order no.****1** **378.305**

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

Diamantjet - diamond cutting disc, standard, concrete



Fast, long-life universal cutting disc, suitable for concrete and stone

Dimensions	QTY/PKG:	Order no.
------------	----------	-----------

in mm:

125 Ø x 22,2	1	349.046
--------------	---	---------

Diamantjet - diamond cutting disc, super premium, concrete



Extremely fast, long-life precision cutting disc, suitable for cutting all construction materials, including concrete, granite and natural stone. Low-noise and transparent.

Dimensions	QTY/PKG:	Order no.
------------	----------	-----------

in mm:

125 Ø x 22,2	1	348.996
--------------	---	---------

Diamantjet - diamond cutting disc, premium, tile



Fast, long-life tile cutting disc with closed diamond segment. Suitable for cutting all tiles, marble, slate, granite and natural stone. Precision cutting and low-noise

Dimensions	QTY/PKG:	Order no.
------------	----------	-----------

in mm:

125 Ø x 22,2	1	349.038
--------------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

Flap disc for metal and stainless steel, cambered



Ideal for flap-grinding metals, stainless steel, alloyed and non-alloyed steel, light metals, non ferrous metals, construction steel and cast iron. Removing welding spots and beads, processing welding seams, breaking and rounding edges. High material removal rate, guarantees effortless working without filling pores.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

125 Ø x 22,2	P 60	10	349.925
--------------	------	----	---------

125 Ø x 22,2	P 80	10	349.933
--------------	------	----	---------

SC-VL polishing flap wheel for metal and stainless steel, cambered



Polishing flap wheel for sanding, cleaning and finishing on stainless steel, steel, titanium alloys, light metals, non-ferrous metals and plastics. Remove any tarnish, flash rust, scale and scratches. Remove any tarnish, flash rust, scale and scratches. Preparing, grinding and polishing welds.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

125 Ø x 22,2	coarse	5	367.494
--------------	--------	---	---------

125 Ø x 22,2	medium	5	358.606
--------------	--------	---	---------

125 Ø x 22,2	fine	5	367.486
--------------	------	---	---------