

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Angle grinders

### L 1506 VR

**Order no. 266.930**

Technical attributes	L 1506 VR
Max. disc diameter	125 mm
No load speed	2200-6800 rpm
Power input	1200 watt
Power output	700 watt
Weight	1,9 kg

#### 1200 watt angle grinder, 125 mm

- VR full-wave electronic control: tachogenerator constant speed control, soft start, overload protection and speed selection
- Highly efficient and resilient motor for more power output
- Spindle lock
- This machine is also available in 110 V

Standard equipment	
1 side handle	194.034
1 guard 125 Ø	267.503
1 pin wrench	100.110
1 clamping nut M14	100.080
1 clamping flange	191.612
1 hook and loop backing pad 115 Ø	

#### Accessories

#### Flap disc for metal and stainless steel, cambered



Ideal for flap-grinding metals, stainless steel, alloyed and non-alloyed steel, light metals, non ferrous metals, construction steel and cast iron. Removing welding spots and beads, processing welding seams, breaking and rounding edges. High material removal rate, guarantees effortless working without filling pores.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
125 Ø x 22,2	P 60	10	349.925
125 Ø x 22,2	P 80	10	349.933

#### FixTec quick clamp nut M 14



For tool-less disc change, suitable for discs from Ø 115-150 mm.

QTY/PKG:	Order no.
1	313.459

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Angle grinders

### SDS-Clc quick-clamp nut



For tool-less disc change suitable for discs from Ø 150-230 mm.

QTY/PKG:	Order no.
----------	-----------

1	253.049
---	---------

### Small metal carrying case



For all angle grinders with disc Ø up to 125 mm.

QTY/PKG:	Order no.
----------	-----------

1	303.224
---	---------

### SC-VL polishing flap wheel for metal and stainless steel, cambered



Polishing flap wheel for sanding, cleaning and finishing on stainless steel, steel, titanium alloys, light metals, non-ferrous metals and plastics. Remove any tarnish, flash rust, scale and scratches. Remove any tarnish, flash rust, scale and scratches. Preparing, grinding and polishing welds.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

125 Ø x 22,2	medium	5	358.606
--------------	--------	---	---------

125 Ø x 22,2	fine	5	367.486
--------------	------	---	---------

125 Ø x 22,2	coarse	5	367.494
--------------	--------	---	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Angle grinders

### Velcro backing M 14



Elastic backing pad with velcro cover.

Dimensions in mm:	Designation:	QTY/PKG:	Order no.
----------------------	--------------	----------	-----------

125 Ø	Velcro bowl	1	231.983
-------	-------------	---	---------

### Hook and loop backing pad "Hook"



Backing pad with foamed base and hook fasteners. Uniform distribution of pressure for sanding and polishing.

Dimensions in mm:	Designation:	QTY/PKG:	Order no.
----------------------	--------------	----------	-----------

125 Ø x M 14	Velcro hook	1	364.584
--------------	-------------	---	---------

### Velcro pad, cushioned M14



12 mm cell rubber for even pressure distribution for grinding, polishing or sealing.

Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

125 Ø	1	350.737
-------	---	---------