

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

L 3309 FR

Order no. 296.805

Technical attributes	L 3309 FR
Max. disc diameter	125 mm
No load speed	11000 rpm
Power input	1010 watt
Power output	610 watt
Tool fixture	M 14
Weight	1,9 kg

1010 watt angle grinder, 125 mm

- FR microprocessor control: tachogenerator constant speed control, soft start, restart protection after power failure, overload protection, temperature monitoring
- Highly efficient and resilient motor for more power output
- Lightweight, ergonomic design
- SoftVib handgrip with integrated, patented locknut wrench and vibration damping
- Patented (DE10115635C1) tool-free adjustable safety guard
- Spindle lock
- This machine is also available in 110 V

Standard equipment	
1 guard 125 Ø	294.438
1 SoftVib handle	316.857
1 clamping flange	
1 FixTec quick-clamp nut M 14	313.459

Accessories

FixTec quick clamp nut M 14



For tool-less disc change, suitable for discs from Ø 115-150 mm.

QTY/PKG: Order no.**1 313.459**

SDS-Clie quick-clamp nut



For tool-less disc change suitable for discs from Ø 150-230 mm.

QTY/PKG: Order no.**1 253.049**

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

Small metal carrying case



For all angle grinders with disc Ø up to 125 mm.

QTY/PKG:	Order no.
----------	-----------

1	303.224
---	---------

SoftVib side handle



SoftVib handle with integral, patented pin wrench (DE10117835A1) and vibration cushioning, significantly reducing the vibration transmitted to hands and arms.

Type:	QTY/PKG:	Order no.
-------	----------	-----------

M 8 with wrench	1	316.857
-----------------	---	---------

Diamantjet - diamond cutting disc, standard, concrete



Fast, long-life universal cutting disc, suitable for concrete and stone

Dimensions in mm:	QTY/PKG:	Order no.
-------------------	----------	-----------

125 Ø x 22,2	1	349.046
--------------	---	---------

Diamantjet - diamond cutting disc, super premium, concrete



Extremely fast, long-life precision cutting disc, suitable for cutting all construction materials, including concrete, granite and natural stone. Low-noise and transparent.

Dimensions in mm:	QTY/PKG:	Order no.
-------------------	----------	-----------

125 Ø x 22,2	1	348.996
--------------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

Diamantjet - diamond cutting disc, premium, tile



Fast, long-life tile cutting disc with closed diamond segment. Suitable for cutting all tiles, marble, slate, granite and natural stone. Precision cutting and low-noise

Dimensions	QTY/PKG:	Order no.
in mm:		

125 Ø x 22,2	1	349.038
--------------	---	---------

Thin cutting disc for stainless steel



Straight, for fast low-force cutting of thin-walled pipes, profiles and plates. Reduced cutting pressure and extremely low chipping for cool cutting. Ensures burr-free edges and prevents blue discoloration. 30% longer service life by packaging in stay-fresh can.

Dimensions	QTY/PKG:	Order no.
in mm:		

125 Ø x 1 x 22,2	10	349.836
---------------------	----	---------

Flap disc for metal and stainless steel, cambered



Ideal for flap-grinding metals, stainless steel, alloyed and non-alloyed steel, light metals, non ferrous metals, construction steel and cast iron. Removing welding spots and beads, processing welding seams, breaking and rounding edges. High material removal rate, guarantees effortless working without filling pores.

Dimensions	Grit:	QTY/PKG:	Order no.
in mm:			

125 Ø x 22,2	P 60	10	349.925
125 Ø x 22,2	P 80	10	349.933

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

SC-VL polishing flap wheel for metal and stainless steel, cambered



Polishing flap wheel for sanding, cleaning and finishing on stainless steel, steel, titanium alloys, light metals, non-ferrous metals and plastics. Remove any tarnish, flash rust, scale and scratches. Remove any tarnish, flash rust, scale and scratches. Preparing, grinding and polishing welds.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

125 Ø x 22,2	medium	5	358.606
125 Ø x 22,2	fine	5	367.486
125 Ø x 22,2	coarse	5	367.494