

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

L 3709/125**Order no. 334.987****800 watt angle grinder, 125 mm**

- Extensive dust protection for motor and gears
- Lightweight, ergonomic design, short and versatile
- Spindle lock
- Side handgrip
- Tool-free adjustment of safety guard

Technical attributes	L 3709/125
Max. disc diameter	125 mm
No load speed	10000 rpm
Power input	800 watt
Power output	470 watt
Tool fixture	M 14
Weight	1,8 kg

Standard equipment	
1 guard 125 Ø	335.266
1 handle	335.274
1 clamping flange	
1 clamping nut M14	
1 pin wrench	

Accessories**FixTec quick clamp nut M 14**

For tool-less disc change, suitable for discs from Ø 115-150 mm.

QTY/PKG: Order no.**1 313.459****SDS-Clic quick-clamp nut**

For tool-less disc change suitable for discs from Ø 150-230 mm.

QTY/PKG: Order no.**1 253.049**

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

Small metal carrying case



For all angle grinders with disc Ø up to 125 mm.

QTY/PKG:	Order no.
----------	-----------

1	303.224
---	---------

Diamantjet - diamond cutting disc, standard, concrete



Fast, long-life universal cutting disc, suitable for concrete and stone

Dimensions	QTY/PKG:	Order no.
in mm:		

125 Ø x 22,2	1	349.046
--------------	---	---------

Diamantjet - diamond cutting disc, super premium, concrete



Extremely fast, long-life precision cutting disc, suitable for cutting all construction materials, including concrete, granite and natural stone. Low-noise and transparent.

Dimensions	QTY/PKG:	Order no.
in mm:		

125 Ø x 22,2	1	348.996
--------------	---	---------

Diamantjet - diamond cutting disc, premium, tile



Fast, long-life tile cutting disc with closed diamond segment. Suitable for cutting all tiles, marble, slate, granite and natural stone. Precision cutting and low-noise

Dimensions	QTY/PKG:	Order no.
in mm:		

125 Ø x 22,2	1	349.038
--------------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

Thin cutting disc for stainless steel



Straight, for fast low-force cutting of thin-walled pipes, profiles and plates. Reduced cutting pressure and extremely low chipping for cool cutting. Ensures burr-free edges and prevents blue discoloration. 30% longer service life by packaging in stay-fresh can.

Dimensions	QTY/PKG:	Order no.
in mm:		

125 Ø x 1 x 22,2	10	349.836
------------------	----	---------

Flap disc for metal and stainless steel, cambered



Ideal for flap-grinding metals, stainless steel, alloyed and non-alloyed steel, light metals, non ferrous metals, construction steel and cast iron. Removing welding spots and beads, processing welding seams, breaking and rounding edges. High material removal rate, guarantees effortless working without filling pores.

Dimensions	Grit:	QTY/PKG:	Order no.
in mm:			

125 Ø x 22,2 P 60		10	349.925
125 Ø x 22,2 P 80		10	349.933

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

SC-VL polishing flap wheel for metal and stainless steel, cambered



Polishing flap wheel for sanding, cleaning and finishing on stainless steel, steel, titanium alloys, light metals, non-ferrous metals and plastics. Remove any tarnish, flash rust, scale and scratches. Remove any tarnish, flash rust, scale and scratches. Preparing, grinding and polishing welds.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

125 Ø x 22,2	medium	5	358.606
--------------	--------	---	---------

125 Ø x 22,2	fine	5	367.486
--------------	------	---	---------

125 Ø x 22,2	coarse	5	367.494
--------------	--------	---	---------

Carry case



Without insert. For the machines L 3709, LE 9-10 125, L 10-10 125 select insert no. 378.305. For the machines OS/OSE 80-2, OD/ODE 100-2, ORE 125-2 select insert no. 379.387.

Size (W x L x H):	QTY/PKG:	Order no.
--------------------	----------	-----------

360 x 228 x 135	1	376.094
-----------------	---	---------

Case insert

Matching insert for carry case 376.094. For angle grinders L 3709, L 10-10 125 and LE 9-10 125.

QTY/PKG:	Order no.
----------	-----------

1	378.305
---	---------