Bahnhofstrasse 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



L 602 VR

220 mm

Polishers

L 602 VR

Order no. 329.800



No load speed	400-2400 rpm
Power input	1500 watt
Power output	1000 watt
Tool fixture	M 14
Weight	3,3 kg

Max. back-up pad diameter 175 mm

Technical attributes

Max. polishing pad

diameter

Variable-speed polisher with a high torque

- VR electronics: stepless speed selection, constant speed control by means of tachogenerator, overload protection and temperature monitor
- · Accelerator switch for a slow and gentle start
- Powerful 1500 watt motor with high degree of efficiency
- · Integrated air deflection: protects against direct air flow
- · Perfect cooling for heavy-duty use.
- Optimum handling by balanced weight distribution and 3 grip variants, depending on use
- Rubber rest bar protects machine and surface of workpiece when changing pads
- Spindle lock

Accessories

Microfibre polishing cloth, classic



Seamless, washable. For gentle removing polishing and sealing residues. For a perfect surface finish and brilliant deep gloss.

Dimensions	QTY/PKG:	Order no.
in mm:		
400 x 400	1	317.098

Standard equipment	
1 side handle	252.721
1 bail handle	287.709



Polishers

Microfibre polishing cloth, premium



Thanks to the very high soft pile, residues can be picked up reliably and gently. This is what makes the microfibre cloth ideal for an optimum paint finish. It can also be used for car wash purposes. Long service life, washing machine safe (without softener).

Dimensions in mm:	QTY/PKG:	Order no.
400 x 400	1	376.531

Backed fleece



Fibre-back and M 14 threaded flange for removing scratches in glass, stainless steel, acrylic and high-gloss polishing of stainless steel. Use only with the respective polishing mediums.

Dimensions	QTY/PKG:	Order no.
in mm:		
125 Ø	1	122.726
175 Ø	1	122.734

Spare fleece



With fiber backing.

Dimension	s QTY/PKG:	Order no.	
in mm:			
125 Ø	1	122.742	
175 Ø	1	122.750	



Polishers

Velcro backing M 14



Elastic backing pad with velcro cover.

Dimensions in mm:	Type:	QTY/PKG:	Order no.
125 Ø	Velcro bowl	1	231.983

Polishing sponge, blue



Sponge of a medium-hard, coarse foam structure and high resistance to tearing. With setback velour for assured polishing and as a centering aid. Particularly for weathered, dull paints and for scratches in combination with the fine polishing compound.

Dimensions in mm:	QTY/PKG:	Order no.
140 Ø x 30	1	376.388
160 Ø x 30	1	376.396
200 Ø x 30	1	376.418

Polishing sponge, white



Sponge of a medium-hard, fine foam structure and highly resistant to tearing. With setback velour for assured polishing and as a centering aid. Particularly for removing minor traces of wear and streaks in combination with the fine polishing compound.

Dimensions in mm:	QTY/PKG:	Order no.
140 Ø x 30	1	376.426
160 Ø x 30	1	376.434
200 Ø x 30	1	376.442

Bahnhofstrasse 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Polishers

Polishing sponge, black



Sponge of an extremely soft and fine foam structure. With setback velour for assured polishing and as a centering aid. Ideally suited - together with the fine polishing compound - for removing holograms and also for paint care and sealing in combination with the high-gloss polish.

Dimensions in mm:	QTY/PKG:	Order no.
140 Ø x 30	1	376.450
160 Ø x 30	1	376.469
200 Ø x 30	1	376.477

Polishing sponge wafer, black



Wafer sponge of an extremely soft and fine foam structure. The special PerfectTouch sandwich design and extra firm white foam layer give the pad much more stiffness and it does not compress so easily. As a result, holograms and micro-scratches, in particular, can be more efficiently and reliably removed. The special design also extends the service life of the polishing disc. With setback velour for assured polishing and as a centering aid. Ideally suited - together with the fine polishing compound - for removing holograms and also for paint care and sealing in combination with the high-gloss polish.

Dimensions in mm:	QTY/PKG:	Order no.
140 Ø x 30	1	376.485
160 Ø x 30	1	376.493
200 Ø x 30	1	376.507

Bahnhofstrasse 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Polishers

Velcro pad, cushioned M 14



12 mm cell rubber for even pressure distribution for grinding, polishing or sealing.

Dimensions	QTY/PKG:	Order no.
in mm:		
125 Ø	1	350.737
	1	
150 Ø	1	350.745

Velcro backed, classic



The pad consists of 90 % lambswool and 10 % polyester. This composition provides for more stability and volume. For great polishing effect in combination with the fine polishing compound.

Dimensions in mm:	QTY/PKG:	Order no.
150 Ø	1	342.521
200 Ø	1	350.265

Polishing sponge



Sponge with medium-hard and coarse foam structure. The large diameter and the frisbee shape is perfect for large areas, e.g. in the maritime and aviation areas. Particularly suitable for weathered and mat paintwork, in conjunction with the fine polishing compound.

Dimensions	QTY/PKG:	Order no.	
in mm:			
220 Ø x 20	1	256.908	

Bahnhofstrasse 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Polishers

Velcro sponge, white (soft)



Sponge with medium-hard and fine foam structure. The large diameter and the frisbee shape is perfect for large areas, e.g. in the maritime and aviation areas. Particularly suitable for removing minor signs of use and streaks in conjunction with the fine polishing compound.

Dimensions	QTY/PKG:	Order no.	
in mm:			
220 Ø x 30	1	256.909	

Polishing lambswool, premium



Polishing lambswool consisting of 90% natural wool and 10% polyester. This combination provides for longer service life and greater volume. And it can remove sanding scratches, for example, 30% faster than with using a sponge. Ideal for UV paints and the latest generation of scratch-resistant paints. For a great polishing effect in combination with the fine polishing compound. The special PerfectTouch sandwich design and extra orange foam layer gives the pad that slight degree of cushioning and much greater stiffness. This allows for a perfect surface contact even in problem areas and an optimal and exact guiding.

Dimensions in mm:	G QTY/PKG:	Order no.
140 Ø	1	376.515
160 Ø	1	376.523

Bahnhofstrasse 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Polishers

Polishing compound



Silicone-free fine polishing compound with high removal and medium gloss level. For the removal of e.g. trapped dust, paint mist, sanding marks in conjunction with the lambswool. In combination with the appropriate sponge ideally suited for removing signs of use, restoring weathered paintwork and eliminating holograms.

Contents:	QTY/PKG:	Order no.
250 ml	1	403.369

High-gloss polish



Silicone-free high-gloss polish with very low dust generation. For polishing new to matt and lightly scratched paintwork. On account of the new nano sanding tool also ideal for scratch-resistant paintwork. Paintwork will have a perfect finish if it was pretreated with the abrasive polish P 05/04-LD.

Contents:	QTY/PKG:	Order no.
250 ml	1	403.377

Bahnhofstrasse 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Polishers

Polishing fleece



Traditional frisbee-shaped polishing fleece made of 100% natural wool. With its large diameter and frisbee shape this polishing fleece is perfect for processing large areas in the maritime and aviation areas. For high polishing effect in conjunction with the fine polishing compound.

Dimension	s QTY/PKG:	Order no.
in mm:		
230 Ø	1	398.632

Lambswool bonnet



Lambswool bonnet with tightening cord, suitable for elastic backing pad. Made of 100% lambswool. For efficient processing of polishing pastes.

Dimensions	QTY/PKG:	Order no.
in mm:		
180 Ø	1	123.870

Flexible backing pad



Backing pad from cellular rubber with rounded edges, for lambswool bonnet. Ensures for even pressure when polishing. M14 thread.

Dimensions	QTY/PKG:	Order no.	
in mm:			
175 Ø	1	123.862	