

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Surface finishing sanding, random orbital

ODE 100-2

Order no. 379.050

**Delta sander with speed control**

- Sanding speed to suit the material due to speed control. No more damaged workpieces.
- Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- Small and particularly light one-handed unit with excellent ergonomics and special balancing for low-vibration operation to make work effortless and reduce the stress on joints of the user
- Integrated dust extraction and reliable disposal of the sanding dust using large volume filter bag made of tear-resistant paper. The filter bag is protected by an impact-resistant plastic cassette case
- Possible to connect external dust extraction
- High-performance sanding wheel: highly durable and abrasion-resistant
- Especially for sanding on corners and edges
- Especially suitable for overhead work

Technical attributes	ODE 100-2
Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing plate	100 x 150 mm
Sanding media fixing	hook and loop
Dust extraction connection	Ø 27 mm
Weight	1,2 kg

Standard equipment

1 velcro backing plate	379.360
1 filter cassette + 1 filter bag	