

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Surface finishing sanding, random orbital

ODE 100-2 Set

Order no. 379.085



Technical attributes	ODE 100-2 Set
Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing plate	100 x 150 mm
Sanding media fixing	hook and loop
Dust extraction connection	Ø 27 mm
Weight	1,2 kg

Delta sander with speed control in set

- Sanding speed to suit the material due to speed control. No more damaged workpieces.
- Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- Small and particularly light one-handed unit with excellent ergonomics and special balancing for low-vibration operation to make work effortless and reduce the stress on joints of the user
- Integrated dust extraction and reliable disposal of the sanding dust using large volume filter bag made of tear-resistant paper. The filter bag is protected by an impact-resistant plastic cassette case
- Possible to connect external dust extraction
- High-performance sanding wheel: highly durable and abrasion-resistant
- Especially for sanding on corners and edges
- Especially suitable for overhead work

Standard equipment

1 velcro backing plate

1 filter cassette + 1 filter bag

Sanding paper SELECTFLEX
25x P 80, 25x P 120

Carry case

Case insert

Accessories

Velcro backing pad Delta



Delta backing plate made of tough special material with extraction perforation.

Designation: Dimensions QTY/PKG: Order no.
in mm:

SP			
100x150-7	100 x 150	1	379.360

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Surface finishing sanding, random orbital

Adapter



Universal adapter with 32 mm thread inside for universal connection of machines with 25-32 mm Ø extraction connection with 32 mm suction hose (without clip attachment), adapter can be trimmed to 3 different diameters.

QTY/PKG:	Order no.
----------	-----------

1	259.827
---	---------

Paper filter bags



Filter bags made of tear-resistant paper for OSE/ODE/ORE.

QTY/PKG:	Order no.
----------	-----------

5	379.336
---	---------

Antistatic suction hose



Antistatic suction hose Ø 27 mm x 4 m with connections for vacuum cleaner and power tool with rotary coupling.

Dimensions	QTY/PKG:	Order no.
in mm:		

27 Ø x 4m	1	379.395
-----------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Surface finishing sanding, random orbital

Velcro sanding paper SELECTFLEX



Ideally suited to redevelopment, renovation and modernisation, especially for working paints, varnishes, stopping, filler.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

100 x 150	P 40	50	380.970
100 x 150	P 60	50	380.989
100 x 150	P 80	50	380.997
100 x 150	P 100	50	381.004
100 x 150	P 120	50	381.012
100 x 150	P 150	50	381.020
100 x 150	P 180	50	381.039
100 x 150	P 220	50	381.047
100 x 150	P 320	50	381.055
100 x 150	P 400	50	381.063

Velcro sanding paper PURFLEX



Ideally suited to working wood and metal.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

100 x 150	P 40	50	381.071
100 x 150	P 60	50	381.098
100 x 150	P 80	50	381.101
100 x 150	P 100	50	381.128
100 x 150	P 120	50	381.136
100 x 150	P 150	50	381.144
100 x 150	P 180	50	381.152

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Surface finishing sanding, random orbital

Velcro sanding fleece MESHFLEX



Ideally suited to roughing, cleaning, degreasing, matt finishing on all materials.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

100 x 150	A 100	5	381.160
-----------	-------	---	---------

100 x 150	A 280	5	381.179
-----------	-------	---	---------

100 x 150	S 1500	5	381.187
-----------	--------	---	---------

Carry case



Without insert. For the machines L 3709, LE 9-10 125, L 10-10 125 select insert no. 378.305. For the machines OS/OSE 80-2, OD/ODE 100-2, ORE 125-2 select insert no. 379.387.

Size (W x L x QTY/PKG: H):	Order no.
--------------------------------	-----------

360 x 228 x 135	1 376.094
--------------------	-----------

Case insert

Suitable insert for carry case 376.094. For OS/OSE 80-2, OD/ODE 100-2, ORE 125-2.

QTY/PKG:	Order no.
----------	-----------

1	379.387
---	---------