

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Surface finishing sanding, random orbital

OSE 80-2 Set

Order no. 379.158

**Palm sander with speed control in set**

- Sanding speed to suit the material due to speed control. No more damaged workpieces.
- Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- Small and particularly light one-handed unit with excellent ergonomics and special balancing for low-vibration operation to make work effortless and reduce the stress on joints of the user
- Integrated dust extraction and reliable disposal of the sanding dust using large volume filter bag made of tear-resistant paper. The filter bag is protected by an impact-resistant plastic cassette case
- Possible to connect external dust extraction
- High-performance sanding wheel: highly durable and abrasion-resistant
- Especially for sanding small surfaces and edges
- Especially suitable for overhead work

Technical attributes	OSE 80-2 Set
Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing plate	80 x 130 mm
Sanding media fixing	hook and loop
Dust extraction connection	Ø 27 mm
Weight	1,2 kg

Standard equipment1 velcro backing plate,
80x130 8F1 filter cassette + 1 filter
bagSanding paper SELECTFLEX
25x P 80, 25x P 120

Carry case

Case insert

Accessories**Adapter**

Universal adapter with 32 mm thread inside for universal connection of machines with 25-32 mm Ø extraction connection with 32 mm suction hose (without clip attachment), adapter can be trimmed to 3 different diameters.

QTY/PKG: **Order no.****1** **259.827**

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Surface finishing sanding, random orbital

Velcro backing pad



Standard backing plate made of tough special material with extraction perforation (8x). Distance between centres of series of holes 54 mm. Extraction perforation FLEX and Festool.

Designation:	Dimensions	QTY/PKG:	Order no.
in mm:			

SP	80 x 130	1	379.344
80x130-8F			



Backing plate made of tough special material with extraction perforation (8x). Distance between centres of series of holes 42 mm. Extraction perforation Rupes and 3M.

Designation:	Dimensions	QTY/PKG:	Order no.
in mm:			

SP	80 x 130	1	379.352
80x130-8R			

Paper filter bags



Filter bags made of tear-resistant paper for OSE/ODE/ORE.

QTY/PKG:	Order no.
----------	-----------

5	379.336
---	---------

Antistatic suction hose



Antistatic suction hose Ø 27 mm x 4 m with connections for vacuum cleaner and power tool with rotary coupling.

Dimensions	QTY/PKG:	Order no.
in mm:		

27 Ø x 4m	1	379.395
-----------	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Surface finishing sanding, random orbital

Velcro sanding paper SELECTFLEX



Ideally suited to redevelopment, renovation and modernisation, especially for working paints, varnishes, stopping, filler.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

80 x 133	P 40	50	380.741
80 x 133	P 60	50	380.768
80 x 133	P 80	50	380.776
80 x 133	P 100	50	380.784
80 x 133	P 120	50	380.792
80 x 133	P 150	50	380.806
80 x 133	P 180	50	380.814
80 x 133	P 220	50	380.822
80 x 133	P 320	50	380.830
80 x 133	P 400	50	380.849

Velcro sanding paper PURFLEX



Ideally suited to working wood and metal.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

80 x 133	P 40	50	380.857
80 x 133	P 60	50	380.865
80 x 133	P 80	50	380.873
80 x 133	P 100	50	380.881
80 x 133	P 120	50	380.903
80 x 133	P 150	50	380.911
80 x 133	P 180	50	380.938

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Surface finishing sanding, random orbital

Velcro sanding fleece MESHFLEX



Ideally suited to roughing, cleaning, degreasing, matt finishing on all materials.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
----------------------	-------	----------	-----------

80 x 133	A 100	5	380.946
----------	-------	---	---------

80 x 133	A 280	5	380.954
----------	-------	---	---------

80 x 133	S 1500	5	380.962
----------	--------	---	---------

Carry case



Without insert. For the machines L 3709, LE 9-10 125, L 10-10 125 select insert no. 378.305. For the machines OS/OSE 80-2, OD/ODE 100-2, ORE 125-2 select insert no. 379.387.

Size (W x L x QTY/PKG: H):	Order no.
--------------------------------	-----------

360 x 228 x 135	1 376.094
--------------------	-----------

Case insert

Suitable insert for carry case 376.094. For OS/OSE 80-2, OD/ODE 100-2, ORE 125-2.

QTY/PKG:	Order no.
----------	-----------

1	379.387
---	---------