

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Surface finishing sanding, random orbital

### OSE 80-2

Order no. 379.034



Technical attributes	OSE 80-2
Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing plate	80 x 130 mm
Sanding media fixing	hook and loop
Dust extraction connection	Ø 27 mm
Weight	1,2 kg

#### Palm sander with speed control

- Sanding speed to suit the material due to speed control. No more damaged workpieces.
- Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- Small and particularly light one-handed unit with excellent ergonomics and special balancing for low-vibration operation to make work effortless and reduce the stress on joints of the user
- Integrated dust extraction and reliable disposal of the sanding dust using large volume filter bag made of tear-resistant paper. The filter bag is protected by an impact-resistant plastic cassette case
- Possible to connect external dust extraction
- High-performance sanding wheel: highly durable and abrasion-resistant
- Especially for sanding small surfaces and edges
- Especially suitable for overhead work

#### Standard equipment

1 velcro backing plate,  
80x130 8F

1 filter cassette + 1 filter  
bag

#### Accessories

##### Adapter



Universal adapter with 32 mm thread inside for universal connection of machines with 25-32 mm Ø extraction connection with 32 mm suction hose (without clip attachment), adapter can be trimmed to 3 different diameters.

QTY/PKG: Order no.

1 259.827

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Surface finishing sanding, random orbital

### Velcro backing pad

---



Standard backing plate made of tough special material with extraction perforation (8x). Distance between centres of series of holes 54 mm. Extraction perforation FLEX and Festool.

Designation:	Dimensions	QTY/PKG:	Order no.
in mm:			

---

SP 80x130-8F	80 x 130	1	379.344
-----------------	----------	---	---------



Backing plate made of tough special material with extraction perforation (8x). Distance between centres of series of holes 42 mm. Extraction perforation Rupes and 3M.

Designation:	Dimensions	QTY/PKG:	Order no.
in mm:			

---

SP 80x130-8R	80 x 130	1	379.352
-----------------	----------	---	---------

### Paper filter bags

---



Filter bags made of tear-resistant paper for OSE/ODE/ORE.

QTY/PKG:	Order no.
----------	-----------

---

5	379.336
---	---------

### Antistatic suction hose

---



Antistatic suction hose  $\varnothing$  27 mm x 4 m with connections for vacuum cleaner and power tool with rotary coupling.

Dimensions	QTY/PKG:	Order no.
in mm:		

---

27 $\varnothing$ x 4m	1	379.395
-----------------------	---	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Surface finishing sanding, random orbital

### Velcro sanding paper SELECTFLEX

---



Ideally suited to redevelopment, renovation and modernisation, especially for working paints, varnishes, stopping, filler.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
80 x 133	P 40	50	380.741
80 x 133	P 60	50	380.768
80 x 133	P 80	50	380.776
80 x 133	P 100	50	380.784
80 x 133	P 120	50	380.792
80 x 133	P 150	50	380.806
80 x 133	P 180	50	380.814
80 x 133	P 220	50	380.822
80 x 133	P 320	50	380.830
80 x 133	P 400	50	380.849

### Velcro sanding paper PURFLEX

---



Ideally suited to working wood and metal.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
80 x 133	P 40	50	380.857
80 x 133	P 60	50	380.865
80 x 133	P 80	50	380.873
80 x 133	P 100	50	380.881
80 x 133	P 120	50	380.903
80 x 133	P 150	50	380.911
80 x 133	P 180	50	380.938

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Surface finishing sanding, random orbital

### Velcro sanding fleece MESHFLEX

---



Ideally suited to roughing, cleaning, degreasing, matt finishing on all materials.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
80 x 133	A 100	5	380.946
80 x 133	A 280	5	380.954
80 x 133	S 1500	5	380.962

### Carry case

---



Without insert. For the machines L 3709, LE 9-10 125, L 10-10 125 select insert no. 378.305. For the machines OS/OSE 80-2, OD/ODE 100-2, ORE 125-2 select insert no. 379.387.

Size ( W x L x QTY/PKG: H):	Order no.
360 x 228 x 135 1	376.094

### Case insert

---

Suitable insert for carry case 376.094. For OS/OSE 80-2, OD/ODE 100-2, ORE 125-2.

QTY/PKG:	Order no.
1	379.387