

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Polishers

PE 14-1 180

Order no. 395.749



Technical attributes	PE 14-1 180
Max. polishing pad diameter	250 mm
Max. back-up pad diameter	180 mm
No load speed	250-1350 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Size (L x H)	402x117 mm
Weight	2,3 kg

Polisher with high torque for processing large painted surfaces

- VR electronic control: stepless speed selection, tachogenerator-controlled constant speed, overload protection, re-start inhibit and temperature monitoring.
- Powerful 1400 watt motor with highly-efficient ventilator for optimum cooling
- Continuous speed control trigger: for a gentle start (starting speed at setting 1 (250 rpm)) and a lock-on for continuous operation.
- Optimised air ducting for optimum cooling of motor and gear. No annoying exhaust air for the user
- Innovative combination of planetary and angular gears reduces noise to an absolute minimum
- Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- Spindle lock: It is ideally positioned to prevent operating error and does not interfere with the grip area.
- With rubberised resting bar for safe setting down
- Especially for processing large horizontal and vertical areas. For the automotive, maritime and aviation areas
- Polishes at extremely low revolutions and high torque, e.g. for heat-sensitive surfaces
- 4 metres PUR H05-BQF cable: wear-resistant, flexible and highly resistant to cuts and abrasions

Standard equipment

1 handle