Bahnhofstrasse 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Polishers

PE 8-480

Order no. 405.817



Polisher for small areas

- VR electronic control: with tachogenerator constant speed control, soft start, overload protection and speed selection
- Lightweight and easy-to-use on small surfaces, tight spaces
- Spindle lock

Accessories		

Velcro pad, cushioned M 14



 $12\ \mathrm{mm}$ cell rubber for even pressure distribution for grinding, polishing or sealing.

Dimensions	QTY/PKG:	Order no.
in mm:		
75 Ø	1	420.492

Technical attributes	PE 8-4 80
Max. polishing pad diameter	80 mm
Max. back-up pad diameter	75 mm
No load speed	1300-3900 rpm
Power input	800 watt
Power output	350 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	1,8 kg

Standard equipment		
1 side handle	194.034	

Bahnhofstrasse 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Polishers

Polishing sponge, blue



Sponge of a medium-hard, coarse foam structure and high resistance to tearing. With setback velour for assured polishing and as a centering aid. Particularly for weathered, dull paints and for scratches in combination with the fine polishing compound.

Dimensions QTY/PKG: Order no.

in mm:

80 Ø x 30 1 420.468

Polishing sponge, white



Sponge of a medium-hard, fine foam structure and highly resistant to tearing. With setback velour for assured polishing and as a centering aid. Particularly for removing minor traces of wear and streaks in combination with the fine polishing compound.

Dimensions QTY/PKG: Order no.

in mm:

80 Ø x 30 1 420.476

Polishing lambswool, premium



Polishing lambswool consisting of 90% natural wool and 10% polyester. This combination provides for longer service life and greater volume. And it can remove sanding scratches, for example, 30% faster than with using a sponge. Ideal for UV paints and the latest generation of scratch-resistant paints. For a great polishing effect in combination with the fine polishing compound. The special PerfectTouch sandwich design and extra orange foam layer gives the pad that slight degree of cushioning and much greater stiffness. This allows for a perfect surface contact even in problem areas and an optimal and exact guiding.

Dimensions QTY/PKG: Order no.

in mm:

80 Ø 1 420.484

Bahnhofstrasse 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Polishers

Polishing compound



Silicone-free fine polishing compound with high removal and medium gloss level. For the removal of e.g. trapped dust, paint mist, sanding marks in conjunction with the lambswool. In combination with the appropriate sponge ideally suited for removing signs of use, restoring weathered paintwork and eliminating holograms.

Contents:	QTY/PKG:	Order no.
250 ml	1	403.369

High-gloss polish



Silicone-free high-gloss polish with very low dust generation. For polishing new to matt and lightly scratched paintwork. On account of the new nano sanding tool also ideal for scratch-resistant paintwork. Paintwork will have a perfect finish if it was pretreated with the abrasive polish P 05/04-LD.

Contents:	QTY/PKG:	Order no.
250 ml	1	403.377

Bahnhofstrasse 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Polishers

Microfibre polishing cloth, classic



Seamless, washable. For gentle removing polishing and sealing residues. For a perfect surface finish and brilliant deep gloss.

Dimensions QTY/PKG: Order no. in mm:

400 x 400 1 317.098

Microfibre polishing cloth, premium



Thanks to the very high soft pile, residues can be picked up reliably and gently. This is what makes the microfibre cloth ideal for an optimum paint finish. It can also be used for car wash purposes. Long service life, washing machine safe (without softener).

Dimensions QTY/PKG: Order no.

in mm:

400 x 400 1 376.531