

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Surface finishing sanding

SE 14-2 125 Set

Order no. 391.174

Technical attributes	SE 14-2 125 Set
Max. back-up pad diameter	125 mm
No load speed	600-2100 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Dimensions (L x W x H, including extraction hood)	370x170x140 mm
Weight	2,6 kg

SUPRAFLEX, the sanding specialist for metal, stone, painted surfaces, wood

- VR electronic control: stepless speed selection, tachogenerator-controlled constant speed, overload protection, re-start inhibit and temperature monitoring.
- Powerful 1400 watt motor with highly-efficient ventilator for optimum cooling
- Optimised air ducting for optimum cooling of motor and gear. No annoying exhaust air for the user
- Innovative combination of planetary and angular gears reduces noise to an absolute minimum
- Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- Completely cast electronic components prevents damage due to metal dust. Protective guard on the winding end of the armature and plated winding on the armature. The 3-fold winding protection reduces motor wear, increases service life.
- Epoxy-coated winding on the field coil
- Guard with pivoting edge segment
- 4 metres PUR H05-BQF cable: wear-resistant, flexible and highly resistant to cuts and abrasions
- Spindle lock
- Sanding specialist for refurbishing, renovating, modernising, processing stainless steel, metal, natural/artificial stone, painted surfaces

Standard equipment
1 guard hood SG D125 SE
1 Adapter SAD-C D32 AS
1 auxiliary handle SE 14-2 125 M8
1 velcro sanding pad SP D125-8 H/F
1 carry case TK-L BoB-2
1 case insert TKE SE 14-2 125
4 sheets of sandingpaper Ø 125 mm
1 offset face spanner
1 hexagon socket screw key, wrench 4
1 hexagon socket wrench, size 5 long
3 cable clips