

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Polishers

XC 3401 VRG Set

Order no. 334.081**Positive-drive orbital polisher in set**

- VR microprocessor control: with tachogenerator constant speed control, soft start, continuous speed control trigger, restart protection after power failure, overload protection, temperature monitoring and speed selection
- 8 mm orbit for high efficiency
- Permanent direct drive for an even polished surface
- Removable, ergonomic handle and guard for optimum handling in all applications
- Cushioned special hook and loop pad for polishing.
- Low heat generation on the surface makes it ideal for temperature-sensitive paints
- Counterweight for smoother operation
- Low height and low weight
- Spindle lock

Technical attributes	XC 3401 VRG Set
Max. polishing pad diameter	160 mm
Velcro backing pad Ø	140 mm
No load speed	160-480 rpm
Orbit	8 mm
Orbit rate, no load	3200-9600 opm
Power input	900 watt
Power output	590 watt
Weight	2,6 kg

Standard equipment	
1 SoftVib handle	316.857
1 bail handle	333.565
1 special velcro backing pad, 140 Ø	342.637
1 polishing sponge PS-W 160	
1 microfibre polishing cloth MW-C	
1 fine polishing compound P 03/06-LD 250 ml	
1 polishing compound P 05/04-LD 250 ml	
1 set-bag	333.573