

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Angle grinders

### L 1710 FRA

Order no. 259.733



Technical attributes	L 1710 FRA
Max. disc diameter	125 mm
No load speed	10000 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Weight	2,4 kg

#### 1400 watt angle grinder with the extra-slim gear head, 125 mm

- FR full-wave electronic control: tachogenerator constant speed control, soft start, overload protection
- Highly efficient and resilient motor for more power output
- Lightweight design with slimline gear head, ideally suited for use in inaccessible places
- SoftVib handgrip with integrated, patented locknut wrench and vibration damping
- Tool-free adjustment of safety guard
- Spindle lock

Standard equipment	
1 guard grinding 125 Ø	274.658
1 SoftVib handle	316.857
1 clamping flange	
1 clamping nut M14	

#### Accessories

##### Steel wire 0,5 mm

Knot-type, mount M 14

Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

65 Ø	1	124.524
------	---	---------

##### 125 mm cutting guard

With guide block and 32 mm Ø extraction nozzle for cutting discs with 125 mm Ø for flange without groove.

Dimensions in mm:	QTY/PKG:	Order no.
----------------------	----------	-----------

125 Ø	1	254.797
-------	---	---------

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Angle grinders

### FixTec quick clamp nut M 14

---

For tool-less disc change, suitable for discs from Ø 115-150 mm.

**QTY/PKG:    Order no.**

---

**1            313.459**

### SDS-Clie quick-clamp nut

---

For tool-less disc change suitable for discs from Ø 150-230 mm.

**QTY/PKG:    Order no.**

---

**1            253.049**

### Small metal carrying case

---

For all angle grinders with disc Ø up to 125 mm.

**QTY/PKG:    Order no.**

---

**1            303.224**

### SoftVib side handle

---

SoftVib handle with integral, patented pin wrench (DE10117835A1) and vibration cushioning, significantly reducing the vibration transmitted to hands and arms.

**Type:            QTY/PKG:    Order no.**

---

**M 8 with  
wrench            1            316.857**

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Angle grinders

### Steel wire 0,3 mm

---

Corrugated, mount M 14

Dimensions in mm:	QTY/PKG:	Order no.
60 Ø	1	124.516

### Suction hose

---

32 mm internal Ø, with snap coupling, 4.0 m long, temperature resistant to 70 °C, incl. coupling bush for vacuum cleaner, filter-free switching module with snap coupling, vacuum hose extension, 32/28 mm adapter and universal adapter for S 36 and S 36 M.

QTY/PKG:	Order no.
1	297.011

### Diamantjet - diamond cutting disc, standard, concrete

---

Fast, long-life universal cutting disc, suitable for concrete and stone

Dimensions in mm:	QTY/PKG:	Order no.
125 Ø x 22,2	1	349.046

### Diamantjet - diamond cutting disc, super premium, concrete

---

Extremely fast, long-life precision cutting disc, suitable for cutting all construction materials, including concrete, granite and natural stone. Low-noise and transparent.

Dimensions in mm:	QTY/PKG:	Order no.
125 Ø x 22,2	1	348.996

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Angle grinders

### Diamantjet - diamond cutting disc, premium, tile

---

Fast, long-life tile cutting disc with closed diamond segment. Suitable for cutting all tiles, marble, slate, granite and natural stone. Precision cutting and low-noise

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

<b>125 Ø x 22,2</b>	<b>1</b>	<b>349.038</b>
---------------------	----------	----------------

### Thin cutting disc for stainless steel

---

Straight, for fast low-force cutting of thin-walled pipes, profiles and plates. Reduced cutting pressure and extremely low chipping for cool cutting. Ensures burr-free edges and prevents blue discoloration. 30% longer service life by packaging in stay-fresh can.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

<b>125 Ø x 1 x</b>	<b>10</b>	<b>349.836</b>
<b>22,2</b>		

### Flap disc for metal and stainless steel, cambered

---

Ideal for flap-grinding metals, stainless steel, alloyed and non-alloyed steel, light metals, non ferrous metals, construction steel and cast iron. Removing welding spots and beads, processing welding seams, breaking and rounding edges. High material removal rate, guarantees effortless working without filling pores.

**Dimensions Grit: QTY/PKG: Order no.**  
**in mm:**

---

<b>125 Ø x 22,2 P 60</b>	<b>10</b>	<b>349.925</b>
<b>125 Ø x 22,2 P 80</b>	<b>10</b>	<b>349.933</b>

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Angle grinders

### SC-VL polishing flap wheel for metal and stainless steel, cambered

---

Polishing flap wheel for sanding, cleaning and finishing on stainless steel, steel, titanium alloys, light metals, non-ferrous metals and plastics. Remove any tarnish, flash rust, scale and scratches. Remove any tarnish, flash rust, scale and scratches. Preparing, grinding and polishing welds.

<b>Dimensions</b>	<b>Grit:</b>	<b>QTY/PKG:</b>	<b>Order no.</b>
<b>in mm:</b>			
<b>125 Ø x 22,2</b>	<b>medium</b>	<b>5</b>	<b>358.606</b>
<b>125 Ø x 22,2</b>	<b>fine</b>	<b>5</b>	<b>367.486</b>
<b>125 Ø x 22,2</b>	<b>coarse</b>	<b>5</b>	<b>367.494</b>