

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Angle grinders

L 21-6 230

Order no. 391.514



Technical attributes	L 21-6 230
Max. disc diameter	230 mm
No load speed	6500 rpm
Power input	2100 watt
Power output	1250 watt
Tool fixture	M 14
Clamping neck Ø	64 mm
Weight	5,2 kg

2100 watt angle grinder, 230 mm

- Robust motor housing and gearbox housing. Stable and robust steel gearbox as well as a spindle bearing protected by a metal cap also increase reliability and durability
- Ergonomically designed and very slender motor housing provides optimum guidance and handling. An additional vibration damping ring between the motor housing and rear handle reduces the vibrations
- SoftVib handgrip for reduced vibration can be mounted in three positions.
- Rear shaft handle with soft padding for secure grip
- Switch: with lock-off / lock-on switch
- Restart protection after power interruption
- Soft-start: for a soft start without power overloading
- Spindle lock
- Tool-free adjustment of safety guard
- Cutting guard, optional accessory (order no. 389.625)

Standard equipment
1 guard grinding 230 Ø
1 SoftVib handle
1 pin wrench BL 5
1 clamping flange
1 clamping nut M14

Accessories

Diamantjet - diamond cutting disc, standard, concrete



Fast, long-life universal cutting disc, suitable for concrete and stone

Dimensions QTY/PKG: Order no.
in mm:

230 Ø x 22,2 1

349.054

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Angle grinders

SDS-Clc quick-clamp nut



For tool-less disc change suitable for discs from Ø 150-230 mm.

QTY/PKG:	Order no.
----------	-----------

1	253.049
---	---------

SoftVib side handle



SoftVib handle with vibration cushioning, significantly reducing the vibration transmitted to hands and arms and reducing the risk of vibration-related injury to the operator.

Type:	QTY/PKG:	Order no.
-------	----------	-----------

M 14	1	325.384
------	---	---------

Plastic multi-carrying case



Perfect fitting, impact resistant carrying case for L 3206 CD, L 3208 CD, L 21-6 230, L 24-6 230, LD 3206 C, SR 602 VV, SK 602 VV.

QTY/PKG:	Order no.
----------	-----------

1	329.908
---	---------

Sanding guard



Sanding guard, suitable for L 3906 C.

Diameter in mm:	QTY/PKG:	Order no.
-----------------	----------	-----------

230	1	338.729
-----	---	---------

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

Cutting guard



Cutting guard, suitable for L 3906 C.

Diameter in mm:	QTY/PKG:	Order no.
--------------------	----------	-----------

230	1	389.625
-----	---	---------
