

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Angle grinders

### L 24-6 230

**Order no. 391.522**

Technical attributes	L 24-6 230
Max. disc diameter	230 mm
No load speed	6500 rpm
Power input	2400 watt
Power output	1450 watt
Tool fixture	M 14
Clamping neck Ø	64 mm
Weight	5,8 kg

#### 2400 watt angle grinder, 230 mm

- Robust motor housing and gearbox housing. Stable and robust steel gearbox as well as a spindle bearing protected by a metal cap also increase reliability and durability
- Ergonomically designed, very slender motor housing for optimum control and handling
- SoftVib handgrip for reduced vibration can be mounted in three positions.
- Rear shaft handle with soft padding for secure grip
- Switch: with lock-off / lock-on switch
- Restart protection after power interruption
- Soft-start: for a soft start without power overloading
- Spindle lock
- Tool-free adjustment of safety guard
- Cutting guard, optional accessory (order no. 389.625)

Standard equipment
1 guard grinding 230 Ø
1 SoftVib handle
1 pin wrench BL 5
1 clamping flange
1 clamping nut M14