

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

L 24-6 230

Order no. 391.522

| Technical attributes | L 24-6 230 |
|----------------------|------------|
| Max. disc diameter | 230 mm |
| No load speed | 6500 rpm |
| Power input | 2400 watt |
| Power output | 1450 watt |
| Tool fixture | M 14 |
| Clamping neck Ø | 64 mm |
| Weight | 5,8 kg |

2400 watt angle grinder, 230 mm

- Robust motor housing and gearbox housing. Stable and robust steel gearbox as well as a spindle bearing protected by a metal cap also increase reliability and durability
- Ergonomically designed, very slender motor housing for optimum control and handling
- SoftVib handgrip for reduced vibration can be mounted in three positions.
- Rear shaft handle with soft padding for secure grip
- Switch: with lock-off / lock-on switch
- Restart protection after power interruption
- Soft-start: for a soft start without power overloading
- Spindle lock
- Tool-free adjustment of safety guard
- Cutting guard, optional accessory (order no. 389.625)

| Standard equipment |
|------------------------|
| 1 guard grinding 230 Ø |
| 1 SoftVib handle |
| 1 pin wrench BL 5 |
| 1 clamping flange |
| 1 clamping nut M14 |

Accessories

Diamantjet - diamond cutting disc, standard, concrete



Fast, long-life universal cutting disc, suitable for concrete and stone

Dimensions QTY/PKG: Order no.
in mm:

230 Ø x 22,2 1**349.054**

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

SDS-Clc quick-clamp nut



For tool-less disc change suitable for discs from Ø 150-230 mm.

| QTY/PKG: | Order no. |
|----------|-----------|
|----------|-----------|

| | |
|---|---------|
| 1 | 253.049 |
|---|---------|

SoftVib side handle



SoftVib handle with vibration cushioning, significantly reducing the vibration transmitted to hands and arms and reducing the risk of vibration-related injury to the operator.

| Type: | QTY/PKG: | Order no. |
|-------|----------|-----------|
|-------|----------|-----------|

| | | |
|------|---|---------|
| M 14 | 1 | 325.384 |
|------|---|---------|

Plastic multi-carrying case



Perfect fitting, impact resistant carrying case for L 3206 CD, L 3208 CD, L 21-6 230, L 24-6 230, LD 3206 C, SR 602 VV, SK 602 VV.

| QTY/PKG: | Order no. |
|----------|-----------|
|----------|-----------|

| | |
|---|---------|
| 1 | 329.908 |
|---|---------|

Sanding guard



Sanding guard, suitable for L 3906 C.

| Diameter in mm: | QTY/PKG: | Order no. |
|-----------------|----------|-----------|
|-----------------|----------|-----------|

| | | |
|-----|---|---------|
| 230 | 1 | 338.729 |
|-----|---|---------|

FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Angle grinders

Cutting guard



Cutting guard, suitable for L 3906 C.

| Diameter in mm: | QTY/PKG: | Order no. |
|--------------------|----------|-----------|
|--------------------|----------|-----------|

| | | |
|-----|---|---------|
| 230 | 1 | 389.625 |
|-----|---|---------|